



MOSA TF II9 Y J-4x240 LED LIGHTER TOWER WITH GENERATOR 9KW SINGLE-PHASE STAGE V

Product price:

13.005,52 € tax excluded

Product description:

MOSA TF II9 Y J-4x240 LED LIGHT TOWER WITH GENERATOR 9KW SINGLE-PHASE STAGE V

MOSA TF II9 Y J-4x240 LED is a light tower with a generator equipped with a Yanmar 3TNV80F Stage V Diesel engine, with 4 floodlights capable of delivering a output of 240W each.

MOSA TF II9 Y J-4x240 LED is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 9 meters, including 4 stabilization feet to secure the lighttower once opened. The lifting system is operated by a hydraulic system that allows for maximum extension without effort.

A single MOSA TF II9 Y tower can cover an area of 4800 m², ensuring a brighter, safer and more productive site. Thanks to the side handles, located at the base of the pole, it is possible to direct the light beam of the projectors as needed.

MOSA TF II9 Y J-4x240 LED is characterized by extremely compact dimensions and square shape that optimize and facilitate the positioning and transport on mobile vehicles. The base, with 4 adjustable and removable anti-tip stabilizers, guarantees high wind stability.

TECHNICAL FEATURES MOSA TF II9 Y J-4x240 LED

Phase Type: Single Phase

Maximum Power: 11.2 KVA / 9 KW

Continuous Power: 10.2 KVA / 8.2 KW

Maximum Height (mt.): 9



Lighted Area: 4800 m²
Lift: Hydraulic
Lamps: LED
Lights: 4 x 240 W
Transportability: Fixed
Wind Stability (Km/h): 80
Rotation: 340°
Adjustable Stabilizers: 4
Motor: Yanmar 3TNV80F
Motor RPM: 1500 rpm
Emissions Standard: STAGE 5
Fuel: Diesel
Acoustic Pressure: 90 dBA (65 dBA @ 7 m)
Tank Capacity (l): 110
Lights Only Range (h): 230
Lights Only Consumption (l/h): 0.50
Min. Dimensions. (mm): 1780 x 1330 x 2050
Max. (mm): 2210 x 1885 x 9000
Dry weight (Kg): 885

Looking for a lighttower with different technical characteristics? Here you can find the full range of lighttowers MOSA or other specialized brands.

The images are for guidance only.

Product features:

Phase: Single phase
Maximum power single phase (KW): 9
Continuous power single phase (KW): 8.2
Maximum power single phase (KVA): 11.2
Continuous power single phase (KVA): 10.2
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V/ 32A 2P+T / 1 x 230V/ 16A 2P+T
Engine: YANMAR 3TNV80F
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 1267
Number cylinders: 3
Cooling: Water

Type of lamps: LED
Lamps: 4 x 240 W
Telescopic pole: Galvanized
Illuminated area (m²): 4800
Total lumens (Lm): 153476
Lifting System: Hydraulic lifting system
Maximum height (m): 9
Mast rotation: 340°
Open size (mm): 2210 x 1885 x 9000
Length closed (mm): 1780
Width closed (mm): 1330
Height closed (mm): 2050
Transportability: Stationary
Stability to wind (Km/h): 80 Km/h
Fuel tank capacity (L): 110
Consumption (L/h): 0.5
Running time (h): 230
Acoustic power: 90 dB(A)
Acoustic pressure: 65 dB(A) at 7 m
Dry weight (Kg): 885
Silenced: Yes
Super silenced: Yes
Brushes: No