



CGM 200VO-B300 WITH AUTOMATIC CONTROL PANEL

Product description:

CGM 200VO-B300 Single/three-phase 200KVA generator with automatic control panel

The CGM 200VO-B300 is a single/three phase 200KVA generator with a 1500 rpm Volvo diesel engine, compact and easy to use, mounted on a fixed base. This CGM 200VO-B300 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 200VO-B300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 200VO-B300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 35 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 200VO-B300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 200VO-B300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 179.2 KW / 224 KVA

Three-phase continuous power: 160 KW / 200 KVA

Maximum single-phase power: 59.73 KW / 74.67 KVA

Single-phase continuous use power: 53.33 KW / 66.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: VOLVO PENTA TAD 733GE

Engine speed: 1500 rpm

Starting: Electric

Consumption: 35 Lt/h at 75% load

Length: 2800 mm

Width: 1310 mm
Height: 1800 mm
Weight: 2150 Kg
AVR

If you are looking for a product like the CGM 200VO-B300 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 59.73
Continuous power single phase (KW): 53.33
Maximum power single phase (KVA): 74.67
Continuous power single phase (KVA): 66.67
Maximum power three phase (KW): 179.2
Continuous power three phase (KW): 160
Maximum power three phase (KVA): 224
Continuous power three phase (KVA): 200
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: VOLVO PENTA TAD733GE
Emissions Regulations: Stage 2
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 7150
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 108 x 130
Fuel tank capacity (L): 250
Consumption (L/h): 35
Running time (h): 7.1
Length (mm): 2800
Width (mm): 1310

Height (mm): 1800

Dry weight (Kg): 2150

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Volvo