



GREEN POWER GP8000 XM/KM SINGLE-PHASE STAGE V GENERATOR MANUAL START 7,7KVA

Product price:

1.038,00 € tax excluded

Product description:

GREEN POWER GP8000 XM/KM SINGLE-PHASE STAGE V GENERATOR MANUAL START 7,7KVA

The generator GREEN POWER GP8000 XM/KM single-phase is equipped with a gasoline-supply KOHLER CH 440 StageV engine capable of delivering 7,7KVA at 3000 rpm.

The GREENPOWER GP8000 XM/KM generator alternator is the LINZ E1C10 MI model (or equivalent primary brand) and is synchronous, single-phase, with brushes and class H insulation. The GREENPOWER GP8000 XM/KM is equipped with manual recoil start with self winding.

One of the main features of the generator is the motor/alternator coupling in single bearing by means of cone, on electrowelded steel base with interposition of vibration dampers.

The GREENPOWER GP8000 XM/KM generator is compact and easy to maneuver and transport thanks to its compact size, its weight of 83 kg as well as the practical tubular handles. The generator with 6.1-liter tank has a fuel consumption of 2.1 liters/hour at 75% load.

STAGE V EMISSION STANDARDS

The STAGE V standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.

The electrical control panel of the generator is composed of:

- Output sockets: 1 x Schuko 16A 230V / 1 x CEE 32A 230V
- Thermal breaker





- Voltmeter

TECHNICAL FEATURES GREEN POWER GP8000 XM/KM

Phase type: Single-phase

Continuous use power: 7 KVA / 7 KW

Maximum power: 7.7 KVA / 7.7 KW

Motor: KOHLER CH 440

Engine speed: 3000 rpm

Emission regulation: StageV

Starting: Manual recoil

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Socket panel: 1 x Schuko 16A 230V / 1 x CEE 32A 230V

Tank capacity: 7 l

Autonomy at 75% load: 3.0 h

Consumption at 75% load: 2,3 Lt/h

Length: 780 mm

Width: 570 mm

Height: 680 mm

Dry weight: 85 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREEN POWER generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 7.7

Continuous power single phase (KW): 7

Maximum power single phase (KVA): 7.7

Continuous power single phase (KVA): 7

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 32A 230V

Engine: Kohler CH 440

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Manual



Engine capacity (cm³): 429
Number cylinders: 1
Cooling: Air
Alternator: Linz
Poles: 2
Fuel tank capacity (L): 7
Consumption (L/h): 2.3 at 75% of the load
Running time (h): 3 at 75% of the load
Length (mm): 780
Width (mm): 570
Height (mm): 680
Dry weight (Kg): 85
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler