



# GREEN POWER GP 6000XM/HE SINGLE- PHASE GENERATOR STAGE V ELECTRIC START 4,5KVA

Product price:

**1.308,00 € tax excluded**

## Product description:

GREEN POWER GP 6000XM/HE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 4,5KVA

The generator GREEN POWER GP 6000XM/HE single-phase is equipped with a gasoline supplied HONDA GX270 **StageV** engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/HE generator is equipped with electric start and has a low fuel consumption, in fact it consumes only 1.6 liters/hour at 75% load for a range of up to 3.3 hours of operation. Extremely practical sockets and controls facilitate the start-up and operation of the generator, making these operations extremely simple and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 76 kg as well as the practical tubular handles. In addition it is equipped with a practical and convenient electric start system, so that it can be put into operation quickly and easily.

The generator is equipped with a high performance HONDA GX270 StageV engine which allows this machine to deliver a maximum single-phase power of 4.5KVA.

The front panel is composed of:

- Thermal breaker;
- 1 Schuko 16A 230V socket
- 1 CEE 16A 230V socket



---

## TECHNICAL FEATURES GREEN POWER GP 6000XM/HE

Phase Type: Single Phase  
Continuous Use Power: 4.1 KVA / 4.1 KW  
Maximum Power: 4.5 KVA / 4.5 KW  
Motor: HONDA GX270  
Motor RPM: 3000 rpm  
Emissions Standard: StageV  
Boosting: Electric  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V  
Tank capacity: 5.3 l  
Autonomy at 75% load: 3.3 h  
Consumption at 75% load: 1.6 Lt/h  
Length: 780 mm  
Width: 570 mm  
Height: 680 mm  
Dry weight: 76 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 4.5  
Continuous power single phase (KW): 4.1  
Maximum power single phase (KVA): 4.5  
Continuous power single phase (KVA): 4.1  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 16A 230V  
Engine: Honda GX270  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 270  
Number cylinders: 1



---

Cooling: Air  
Alternator: LINZ SP10 MG  
Poles: 2  
Fuel tank capacity (L): 5.3  
Consumption (L/h): 1.6 at 75% of the load  
Running time (h): 3.3 at 75% load  
Length (mm): 570  
Width (mm): 700  
Height (mm): 630  
Dry weight (Kg): 76  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Honda

