



# GREEN POWER GP 6000XM/KE SINGLE- PHASE GENERATOR STAGE V ELECTRIC START 5,5KVA

Product price:

**1.038,00 € tax excluded**

## Product description:

GREEN POWER GP 6000XM/KE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 5,5KVA

The generator GREENPOWER GP 6000XM/KE single-phase generator is equipped with a KOHLER CH 395 **StageV** gasoline-supplied engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/KE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1.8 liters/hour at 75% load for a range of up to 3.9 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 79 kg as well as the practical tubular handles. In addition it is equipped with a practical and convenient electric start system, so it can be put into operation quickly and easily.

The GREENPOWER GP 6000XM/KE generator is equipped with a high performance KOHLER CH 395 StageV engine that allows this machine to deliver a maximum single-phase power of 5.5KVA.

## VOLTAGE REGULATOR

The voltage regulator is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself.

In essence, thanks to this device, the alternating current coming from the alternator is regulated and transformed into direct current at constant voltage.

The front panel of the GREENPOWER GP 6000XM/KE generator consists of:

- Thermal circuit breaker;
- 1 Schuko socket 16A 230V
- 1 CEE socket 16A 230V

#### TECHNICAL FEATURES GREENPOWER GP 6000XM/KE

Phase Type: Single Phase  
Continuous Use Power: 5 KVA / 5 KW  
Maximum Power: 5.5 KVA / 5.5 KW  
Motor: KOHLER CH 395  
Motor RPM: 3000 rpm  
Emissions Standard: Stage V  
Start: Electric  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V  
Tank capacity: 7 l  
Run time at 75% load: 3.9 h  
Consumption at 75% load: 1.8 Lt/h  
Length: 780 mm  
Width: 570 mm  
Height: 680 mm  
Dry weight: 79 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

#### Product features:

Phase: Single phase  
Maximum power single phase (KW): 5.5  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 5.5  
Continuous power single phase (KVA): 5  
Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 16A 230V

Engine: Kohler CH 395, 4 stroke

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 277

Number cylinders: 1

Cooling: Air

Alternator: LINZ SP10 MG

Poles: 2

Fuel tank capacity (L): 7

Consumption (L/h): 1.8 at 75% of the load

Running time (h): 3.9 at 75% load

Length (mm): 570

Width (mm): 780

Height (mm): 680

Dry weight (Kg): 79

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler