



GREEN POWER GP 8000XT/HE SINGLE/THREE PHASE STAGE V GENERATOR ELECTRIC START 7,7KVA

Product price:

1.693,30 € tax excluded

Product description:

GREEN POWER GP 8000XT/HE GENERATOR SINGLE-PHASE / THREE-PHASE STAGE V ELECTRICAL START 7,7KVA

The generator GREENPOWER GP 8000XT/HE single-phase / three-phase , is equipped with a HONDA GX390 **StageV** gasoline-powered engine, and is complete with Compound voltage regulator (**AVR optional**).

GREENPOWER GP 8000XT/HE is equipped with electric start and has a low fuel consumption, in fact it consumes only 2.1 liters/hour at 75% load for a range of up to 2.9 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 95 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient electric start system, so that it can be put into operation quickly and easily.

The GREENPOWER GP 8000XT/HE generator is equipped with a high performance HONDA GX390 StageV engine that allows this machine to deliver a maximum threephase power of 7.7KVA.

VOLTAGE REGULATOR



The voltage regulator is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself.

Basically, thanks to this device, the alternating current coming from the alternator is regulated and transformed into direct current at constant voltage.

The control panel of the GREENPOWER GP 8000XT/HE generator is composed of:

- Output sockets: 1x 230V 16A CEE / 1x 400V 16A CEE
- Thermal circuit breaker
- Voltmeter
- Three-pole magneto-thermal switch

TECHNICAL FEATURES GREENPOWER GP 8000XT/HE

Phase type: Singlephase/Threephase
Continuous use power Singlephase: 3.0 KVA / 2.4 KW
Maximum power Singlephase: 3.3 KVA / 2.7 KW
Continuous use power Threephase: 7.0 KVA / 5.6 KW
Maximum ThreePhase Power: 7.7 KVA / 6.2 KW
Motor: HONDA GX390
Engine RPM: 3000 rpm
Emission Standard: Stage V
Start: Electric
Fuel: Gasoline
Voltage: 230 / 400 V
Frequency: 50 Hz
Socket panel: 1 x CEE 16A 230V / 1 x CEE 16A 400V
Tank capacity: 6.1 l
Autonomy at 75% load: 2.9 h
Consumption at 75% load: 2.1 Lt/h
Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 95 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.7

Continuous power single phase (KW): 2.4

Maximum power single phase (KVA): 3.3

Continuous power single phase (KVA): 3

Maximum power three phase (KW): 6.2

Continuous power three phase (KW): 5.6

Maximum power three phase (KVA): 7.7

Continuous power three phase (KVA): 7

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE

Engine: Honda GX390

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 389

Number cylinders: 1

Cooling: Air

Alternator: LINZ E1S10 MH

Poles: 2

Fuel tank capacity (L): 6.1

Consumption (L/h): 2.1 at 75% of the load

Running time (h): 2.95 at 75% of the load

Length (mm): 780

Width (mm): 570

Height (mm): 680

Dry weight (Kg): 95

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Honda

