



GREEN POWER GP 4000XM/YM SINGLE- PHASE DIESEL GENERATOR STAGEV 3,5KVA

Product price:

1.492,70 € tax excluded

Product description:

GREEN POWER GP 4000XM/YM SINGLE-PHASE DIESEL GENERATOR STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/YM single-phase is equipped with a YANMAR L70AE **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/YM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,2 liter/hour at 75% of load for a range of up to 3 hours of operation.

The GREENPOWER GP 4000XM/YM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 4000XM/YM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 4000XM/YM has a completely steel structure and a tank with a maximum capacity of 3,5 liters. The generator guarantees an efficient and silent operation thanks to the YANMAR L70AE StageV engine that allows to deliver a maximum power of 3,5KVA.

STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but



an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL CHARACTERISTICS GREENPOWER GP 4000XM/YM

Phase Type: Single-phase
Continuous duty power: 3.1 KVA / 3.1 KW
Maximum power: 3.5 KVA / 3.5 KW
Engine: YANMAR L70AE
Engine speed: 3000 rpm
Emission regulation: StageV
Starting: Manual recoil
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 2 x Schuko 16A 230V
Tank capacity: 3,5 l
Autonomy at 75% load: 3 h
Consumption at 75% load: 1,2 Lt/h
Length: 700 mm
Width: 570 mm
Height: 630 mm
Dry weight: 69 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 3.5
Continuous power single phase (KW): 3.1
Maximum power single phase (KVA): 3.5
Continuous power single phase (KVA): 3.1
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 x 230V 16A SCHUKO
Engine: Yanmar L70AE, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000

Starting system: Pull starter with recoil
Engine capacity (cm³): 296
Number cylinders: 1
Cooling: Air
Alternator: LINZ SP10 SE
Poles: 2
Fuel tank capacity (L): 3.5
Consumption (L/h): 1.2 at 75% of the load
Running time (h): 3 at 75% of the load
Length (mm): 570
Width (mm): 700
Height (mm): 630
Dry weight (Kg): 69
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Yanmar