



GREEN POWER GP 6000XT/LM SINGLE- PHASE/THREE-PHASE DIESEL GENERATOR STAGEV 6,5KVA

Product price:

1.947,00 € tax excluded

Product description:

GREEN POWER GP 6000XT/LM SINGLE-PHASE/THREE-PHASE DIESEL GENERATOR STAGEV 6,5KVA

The generator GREENPOWER GP 6000XT/LM single/three-phase is equipped with a KOHLER KD15440 **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XT/LM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,6 liter/hour at 75% of load for a range of up to 3,1 hours of operation.

The GREENPOWER GP 6000XT/LM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 6000XT/LM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 6000XT/LM has a completely steel structure and a tank with a maximum capacity of 5 liters. The generator guarantees an efficient and silent operation thanks to the KOHLER KD15440 StageV engine that allows to deliver a maximum power of 6,5KVA.

STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The



regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL CHARACTERISTICS GREENPOWER GP 6000XT/LM

Phase Type: SinglePhase/Threephase
Singlephase continuous use output: 3.0 KVA / 2.4 KW
Singlephase maximum output: 3.3 KVA / 2.7 KW
Threephase continuous use output: 5.9 KVA / 4.7 KW
Threephase maximum output: 6.5 KVA / 5.2 KW
Motor: KOHLER KD15440
Motor speed: 3000 rpm
Emission regulation: Stage V
Starting: Manual recoil
Fuel: Diesel
Voltage: 230 / 400 V
Frequency: 50 Hz
Socket panel: 1 x CEE 16A 230V / 1 x CEE 16A 400V
Tank capacity: 5 l
Run time at 75% load: 3. 1 h
Consumption at 75% load: 1.6 Lt/h
Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 97 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 2.7
Continuous power single phase (KW): 2.4
Maximum power single phase (KVA): 3.3
Continuous power single phase (KVA): 3
Maximum power three phase (KW): 5.2
Continuous power three phase (KW): 4.7
Maximum power three phase (KVA): 6.5
Continuous power three phase (KVA): 5.9

Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x CEE 16A 230V / 1 x CEE 16A 400V
Engine: Kohler KD 15-440
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Pull starter with recoil
Engine capacity (cm³): 436
Number cylinders: 1
Cooling: Air
Alternator: LINZ E1S10 MH
Poles: 2
Fuel tank capacity (L): 5
Consumption (L/h): 1.6 at 75% of the load
Running time (h): 3.1 at 75% of load
Length (mm): 780
Width (mm): 570
Height (mm): 680
Dry weight (Kg): 97
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler