



GREEN POWER GP 17000 SM/LDE SILENT GENERATOR SINGLE- PHASE ELECTRICAL START 16,3KVA

Product price:

6.006,20 € tax excluded

Product description:

GREEN POWER GP 17000 SM/LDE SILENT GENERATOR SINGLE-PHASE ELECTRICAL START 16,3KVA

The generator GREEN POWER GP 17000 SM/LDE single-phase, is equipped with a KOHLER KD625-2 Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREEN POWER GP 17000 SM/LDE is equipped with electric start and has a low fuel consumption, in fact it consumes only 4 liters/hour at 75% of the load for an autonomy of up to 12,5 hours of operation.

The generator GREEN POWER GP 17000 SM/LDE is equipped with silenced casing that can be opened in two sections made of sheet 20/10, soundproofing material in class 1, internal muffler. Thanks to these devices, the generator can be considered super-silenced, with a noise emission of only 77 dB recorded at a distance of 7 meters from the source.

The generator guarantees efficient and silent operation thanks to the KOHLER KD625-2 engine, which allows to deliver a maximum power of 16,3KVA.

ATS AUTOMATIC STARTING FRAME

The GREEN POWER GP 17000 SM/LDE generator is designed for use with an ATS automatic start-up panel. Thanks to this, you will no longer have to worry about blackouts, in the event of a power failure this panel is able to automatically turn on the generator and allow you to continue your business.





The generator control panel consists of:

- Thermomagnetic circuit breaker and isolation control
- Sockets: 1 x 16A 3P 230V / 1 x 63A 3P 230V
- ATS arrangement
- Voltmeter
- Ammeter
- Hour meter
- Ignition switch
- Emergency stop button

TECHNICAL FEATURES GREEN POWER GP 17000 SM/LDE

Phase Type: Single-phase

Continuous output: 14,8 KVA / 14,8 KW

Maximum output: 16,3 KVA / 16,3 KW

Motor: KOHLER KD625-2

Engine speed: 3000 rpm

Emission regulation: NOT Emitted

Starting: Electric

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Socket panel: 1 x 16A 3P 230V / 1 x 63A 3P 230V

Tank capacity: 50 l

Runtime at 75% load: 12.5 h

Consumption at 75% load: 4 Lt/h

Acoustic pressure: 77 dB(A) @ 7 m

Length: 1200 mm

Width: 700 mm

Height: 1050 mm

Dry weight: 390 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 16.3

Continuous power single phase (KW): 14.8



Maximum power single phase (KVA): 16.3
Continuous power single phase (KVA): 14.8
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 16A 3P 230V / 1 x 63A 3P 230V
Engine: Kohler KD 625/2
Emissions Regulations: Stationary Use
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 1248
Number cylinders: 2
Cooling: Air
Alternator: LINZ E1C13MD/2
Poles: 2
Fuel tank capacity (L): 50
Consumption (L/h): 4 at 75% of the load
Running time (h): 12,5 at 75% load
Acoustic pressure: 77 dB(A) at 7 m
Length (mm): 1200
Width (mm): 700
Height (mm): 840
Dry weight (Kg): 390
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler