



HYUNDAI SUPER-SILENCED SINGLE-PHASE / THREE-PHASE DIESEL GENERATOR 11 KW AVR

Product price:

3.822,86 € tax excluded

Product description:

HYUNDAI SUPER-SILENCED SINGLE-PHASE / THREE-PHASE DIESEL GENERATOR 11 KW AVR

The generator HYUNDAI single/three-phase is equipped with a 954 cc Diesel engine, is able to deliver a power of 11 KW and is complete with AVR voltage regulator.

The HYUNDAI generator is equipped with **electric start** with 12V 45A/h battery and with a low fuel consumption, in fact it consumes only 4.4 liters/hour at 50% of the load, combined with a capacious tank of 53 l of maximum capacity, it will give you an autonomy of about 12 hours.

This generator is equipped with a soundproof cabin, made of carbon steel, bent and electro-welded, with protection class IP23 and openable. This cabin allows the HYUNDAI super-silenced generator set to deliver a sound pressure of only 69 dB(A) @ 7 meters. The generator is predisposed for automatic start-up by means of an ATS panel, which allows automatic ignition in case of blackout.

AUTOMATIC TRANSFER SWITCH ATS

The generator is prearranged for the use of Automatic Transfer Switch ATS. Thanks to which you will no longer have to worry about black-outs because if the mains fails this panel is able to start the generator automatically and allow you to continue your activity without losing your work data.

TECHNICAL FEATURES HYUNDAI GENERATOR

Type of phase: Singlephase / Threephase
Continuous use power: 12.5 KVA / 10 KW
Maximum power: 13.7 KVA / 11 KW
Engine: 4 strokes
Engine revs: 3000 rpm
Emissions regulation Not Emitted
Starting: Electric / Automatic
Fuel: Diesel
Voltage: 230 / 400 V
Frequency: 50 Hz
Socket panel: 1 x 32A / 1 x 63A
Voltage regulator: AVR
Tank capacity: 53 l
Autonomy at 50% load: 12 h
Consumption at 50% load: 4.4 Lt/h
Acoustic pressure: 69 dB(A) @ 7 m
Length: 1200 mm
Width: 800 mm
Height: 1160 mm
Dry weight: 318 Kg

Are you looking for a generating with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11
Continuous power single phase (KW): 10
Maximum power single phase (KVA): 13.75
Continuous power single phase (KVA): 12.5
Maximum power three phase (KW): 11
Continuous power three phase (KW): 10
Maximum power three phase (KVA): 13.75
Continuous power three phase (KVA): 12.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 32A / 1 x 63A
Engine: 4 stroke
Engine rpm (rpm): 3000

Starting system: Electric
Engine capacity (cm³): 954
Oil capacity (L): 3
Fuel tank capacity (L): 53
Consumption (L/h): 4.4
Running time (h): 12 at 50% of the load
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 1200
Width (mm): 800
Height (mm): 1160
Dry weight (Kg): 318
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Hyundai