



# HONDA Outboard BF 135D LCRU SILVER Long Shaft 135 Hp

**Product price:**

**10.750,00 € tax excluded**

## **Product description:**

HONDA Outboard BF 135D LCRU SILVER Long Shaft 135 Hp

Honda BF 135D LCRU outboard engine are perfect for professional use, they are reliable, compact and lightweight complete with PGM-Fi electronic fuel injection system.

HONDA BF 135D LCRU are outboards optimized to offer more power for a wide range of different boats. The firm, smooth power this advanced technology offers is sure to put a smile on your face as you venture out to sea.

The HONDA BF 135D LCRU comes complete with the VTEC™ system that keeps fuel consumption down while delivering an exciting increase in power. First used on Honda's Formula One cars, it delivers increased power and torque at all engine speeds.

The HONDA BF 135D LCRU dual-stage air induction works with a shuttle valve built into the Variable Air Intake (VAI) manifold. When fully open, this valve changes the resonance and airflow generating more torque at low rpm. When the throttle valve is fully open and rpm increases, the cooling valve closes and creates a direct airflow to the engine.

HONDA BF 135D LCRU outboards are NMEA2000® compliant. There is no need to modify the wiring because everything is set up. Simply plug the engine into the CANbus network - the boat's nervous system - for total connectivity and control. Then the engine can be connected to other NMEA devices such as the navigation system, GPS, sonar devices, sounder and chartplotter. All information, including engine data, will be displayed via the multifunctional gauges.

## **TECHNICAL FEATURES HONDA BF 135D LCRU**

Net Power (kW): 99.3

Net Power (Hp): 135

Displacement: 2354 cm<sup>3</sup>



Shaft Length: Long  
Starter: Electric  
Ignition system: Electronic PGM-IG  
Fuel supply: PGM-FI (Programmed electronic injection)  
Engine trim and lift: Electric  
Bore x stroke: 89 x 96 mm  
Engine: Honda DOHC, 4-stroke  
Number of cylinders: 4 in line  
Speed at full throttle (rpm): 5000-6000  
Cooling system: Water  
Battery charge capacity (A): 40  
Propeller rotation: counter-rotating  
Transom height (mm): 508  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1665  
Dry weight (Kg): 214

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the sector.

The images are purely indicative.

#### **Product features:**

Fuel: Gasoline  
Engine: DOHC, 4 tempi  
Ignition: Electronic PGM-IG  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2354  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water (with thermostat)  
Bore x stroke (mm): 87 x 99  
Rpm at full throttle (rpm): 5000 - 6000  
Appearance and engine lifting: Electric  
Transom height (mm): 508  
Net power (kW): 99.3  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1665  
Dry weight (Kg): 214  
Shaft Length: L

Controls: Remote

