



# HYUNDAI LS 65006 GASOLINE GENERATOR SINGLE PHASE / THREE PHASE STAGE V AVR 6 KW

Product price:

**963,03 € tax excluded**

## Product description:

HYUNDAI LS 65006 GASOLINE GENERATOR SINGLE PHASE / THREE PHASE STAGE V AVR 6 KW

The HYUNDAI LS 65006 single/three phase generator, is equipped with a 4-stroke **StageV** engine supplied by gasoline, delivers a maximum power of 6KW, complete with AVR voltage regulator.

HYUNDAI LS 65006 is equipped with electric start with battery and a revolutionary Full Power System, thanks to which the output power is identical in both single-phase and three-phase, unlike standard three-phase generators in which the single-phase power is reduced to 1/3.

The HYUNDAI LS 65006 generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI LS 65006 generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI LS 65006 has a completely steel structure and a tank with a maximum capacity of 25 lt.

## EMISSION STANDARD STAGEV

HYUNDAI LS 65006 is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and

ensure a 200% reduction in environmental impact compared to standard engines.

## TECHNICAL CHARACTERISTICS HYUNDAI LS 65006

Phase type: Singlephase / Threephase  
Continuous use power: 5.5 KVA / 5.5 KW  
Maximum power 6 KVA / 6 KW  
Engine: 4-stroke  
Engine revolutions: 3000 rpm  
Emissions standard: StageV  
Starting: Electric / Manual  
Fuel: Gasoline  
Voltage: 230/400 V  
Frequency: 50Hz  
Socket panel: 1 x CEE 16A 230V / 1 x CEE 32A 400V  
Tank capacity: 25 l  
Sound pressure: 76 dB (A) @ 7 m  
Length: 600 mm  
Width: 860 mm  
Height: 620 mm  
Dry weight: 89 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 6  
Continuous power single phase (KW): 5.5  
Maximum power single phase (KVA): 6  
Continuous power single phase (KVA): 5.5  
Maximum power three phase (KW): 6  
Continuous power three phase (KW): 5.5  
Maximum power three phase (KVA): 6  
Continuous power three phase (KVA): 5.5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x CEE 16A 230V / 1 x CEE 32A 400V  
Engine: 4-stroke

---

Engine rpm (rpm): 3000  
Starting system: Manual / Electric  
Alternator: Copper Winding  
Fuel tank capacity (L): 25  
Acoustic pressure: 76 dB(A) at 7 m  
Length (mm): 860  
Width (mm): 600  
Height (mm): 620  
Dry weight (Kg): 89  
Silenced: Yes  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: AVR