



HONDA OUTBOARD BF 135D LCRU TOTAL WHITE LONG SHAFT 135 Hp

Product price:

10.950,00 € tax excluded

Product description:

HONDA OUTBOARD BF 135D LCRU TOTAL WHITE LONG SHAFT 135 Hp

Honda BF 135D LCRU TOTAL WHITE outboard engines are perfect for professional use, they are reliable, compact and lightweight complete with PGM-Fi electronic fuel injection system.

HONDA BF 135D LCRU are outboards optimized to offer more power for a wide range of different boats. The firm, smooth power this advanced technology offers is sure to put a smile on your face as you venture out to sea.

The HONDA BF 135D LCRU dual-stage air induction system operates with a shuttle valve built into the Variable Air Intake (VAI) manifold. When fully open, this valve changes the resonance and airflow generating more torque at low rpm. When the throttle valve is fully open and rpm increases, the cooling valve closes and creates a direct airflow to the engine.

HONDA BF 135D LCRU outboards are NMEA2000® compliant. There is no need to modify the wiring because everything is set up. Simply plug the engine into the CANbus network - the boat's nervous system - for total connectivity and control. Then the engine can be connected to other NMEA devices such as the navigation system, GPS, sonar devices, sounder and chartplotter. All information, including engine data, will be displayed via the multifunctional gauges.

The Boasting LoW Speed Torque (BLAST) system on the HONDA BF 135D LCRU outboard significantly improves performance and acceleration by automatically anticipating injection times and increasing the air/fuel ratio.

TECHNICAL FEATURES HONDA BF 135D LCRU TOTAL WHITE

Net Power (kW): 99.3

Net Power (Hp): 135

Displacement: 2354 cm³



Shaft Length: Long
Starter: Electric
Ignition system: Electronic PGM-IG
Fuel supply: PGM-FI (Programmed electronic injection)
Engine trim and lift: Electric
Bore x stroke: 89 x 96 mm
Engine: Honda DOHC, 4-stroke
Number of cylinders: 4 in line
Speed at full throttle (rpm): 5000-6000
Cooling system: Water
Battery charge capacity (A): 40
Propeller rotation: Counter-rotating
Transom height (mm): 508
Length (mm): 845
Width (mm): 580
Height (mm): 1665
Dry weight (Kg): 214

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the sector.

Product features:

Fuel: Gasoline
Engine: DOHC, 4 tempi
Ignition: Electronic PGM-IG
Starting system: Electric
Engine capacity (cm³): 2354
Number cylinders: 4
Cylinders' position: In line
Cooling: Water (with thermostat)
Bore x stroke (mm): 87 x 99
Rpm at full throttle (rpm): 5000 - 6000
Appearance and engine lifting: Electric
Transom height (mm): 508
Net power (kW): 99.3
Length (mm): 845
Width (mm): 580
Height (mm): 1665
Dry weight (Kg): 214
Shaft Length: L
Controls: Remote