



# HONDA OUTBOARD BF 150D XRU EXTRA LONG SHAFT 150 HP

**Product price:**

**12.455,00 € tax excluded**

## **Product description:**

HONDA OUTBOARD BF150D XRU EXTRA LONG SHAFT 150 HP

Honda BF150D XRU are outboard engines perfect for professional use, they are reliable, compact and lightweight complete with PGM-IG electronic fuel injection system.

Just press the start & stop button to hear the deep and distinctive sound of the engine. Hand on the throttle and off you go, as the revs increase, these Honda outboards combine boating comfort with exhilarating high-performance thrust with extremely low vibration levels.

VTEC (Variable Valve Timing and Lift Electronic Control) technology available in the HONDA BF150D XRU outboard varies intake valve lift and timing ensuring optimal performance. This technology ensures smooth and stable idle speeds at low rate, while increasing valve lift and timing at high speeds to provide a wider and more optimized torque curve.

The Honda BF150D XRU outboard features BLAST™ ready-to-start technology that gets the engine up to full power in seconds. The BLAST™ (Boosted Low Speed Torque) system delivers high torque even at low rate by unleashing powerful thrust from start-up. The ECU automatically advances the ignition timing, while at the same time increasing the fuel/air ratio to give more thrust from low speed.

Honda BF150D XRU is equipped with special ECOmo poor mixture combustion control system ensures significant fuel economy right from speed and performance. Once at speed, much less fuel is consumed.

HONDA BF150D XRU outboards are NMEA2000® compliant. There is no need to modify the wiring because everything is set up. Simply plug the engine into the CANbus network - the boat's nervous system - for total connectivity and control.

TECHNICAL FEATURES HONDA BF150D XRU

Net Power (kW): 110.3  
Net Power (Hp): 150  
Displacement: 2354 cm<sup>3</sup>  
Shaft Length: Extra Long  
Starter: Electric  
Ignition System: Electronic PGM-IG  
Fuel supply: PGM-FI (Programmed electronic injection)  
Setup and Engine Lift: Electric  
Bore x stroke: 87 x 99 mm  
Engine: Honda DOHC 4-cylinder in-line VTEC™ engine  
Speed at full throttle (rpm): 5000-6000  
Cooling system: Water  
Battery charge capacity (A): 40  
Propeller rotation: Standard  
Transom height (mm): 635  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1790  
Dry weight (Kg): 220

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the sector.

The images are purely indicative.

**Product features:**

Fuel: Gasoline  
Engine: Honda DOHC 4 Cylinder Inline VTEC  
Ignition: Electronic PGM-IG  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2354  
Number cylinders: 4  
Cooling: Water (with thermostat)  
Bore x stroke (mm): 87 x 99  
Reduction ratio: 2.14  
Rpm at full throttle (rpm): 5000 - 6000  
Appearance and engine lifting: Electric  
Transom height (mm): 635  
Net power (kW): 110.3  
Length (mm): 845  
Width (mm): 580  
Height (mm): 1790

---

Dry weight (Kg): 220  
Shaft Length: X  
Controls: Remote