

# THREE-PHASE PTO GENERATOR 30KVA AVR



**Product price:**

**2.768,00 € tax excluded**

## Product description:

### THREE-PHASE PTO GENERATOR 30KVA

The Generator Three-phase PTO is equipped with MECC ALTE ECP28-VL/4 alternator capable of delivering a power of 30KVA, complete with **AVR voltage regulator**.

The generator is very reliable as it has been built and designed using top quality materials. The generator is easy to transport, install and position due to its compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 60 HP and a PTO speed of at least 430 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it is possible to cause malfunctions or in the worst cases damage to the equipment.

These compact, robust and easy to use generators come complete with a 3-point attachment base for safe attachment to any tractor.

The generator is equipped with an electric panel complete with:

- Thermomagnetic circuit breaker
- Differential
- Socket 63 A 400 V
- Socket 16 A 230 V
- E31 digital module complete with: Voltmeter, Frequency meter and Hour meter

## TECHNICAL FEATURES

Phase Type: Three Phase

Continuous output: 30 KVA  
Continuous output: 24 KW  
Voltage: 230 - 400 V  
Frequency: 50 Hz  
Motor RPM: 1500 rpm  
Tractor Power Required: 60 hp  
Power Take-Off RPM: 430 rpm  
Alternator: MECC ALTE ECP28-VL/4 (OR QUIVALENT)  
Number of poles: 4  
Isolation class: H  
Protection class: IP 23  
Voltage regulator: AVR  
Length: 855 mm  
Width: 580 mm  
Height: 985 mm  
Weight: 217 Kg

Are you looking for a PTO generator with different technical characteristics? Here you can find the full range of Green Power or other brands specializing in the field

Images and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Phase: Three phase  
Continuous power three phase (KW): 24  
Continuous power three phase (KVA): 30  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine rpm (rpm): 1500  
Alternator: MECC ALTE ECP28-VL/4  
Poles: 4  
Protection degree: IP23  
PTO speed (round/min): 440  
Required tractor power: 60 Hp  
Length (mm): 855  
Width (mm): 580  
Height (mm): 985  
Dry weight (Kg): 217  
Silenced: No  
Super silenced: No  
Voltage regulator: AVR