



# GENERATOR SINGLE-PHASE DIESEL STAGEV 5,6KVA

Product price:

**1.395,00 € tax excluded**

## Product description:

### GENERATOR SINGLE-PHASE DIESEL STAGEV 5,6KVA

Generator single-phase equipped with a KOHLER 15440 **StageV** diesel-powered engine, and is complete with a capacitor voltage regulator ( **AVR optional** ).

The generator is equipped with a manual recoil starter with self-winding and has a low fuel consumption, in fact it consumes only 1.6 liters / hour at 75% of the load for an autonomy of up to 3.1 hours of operation.

The generator provides reliable power for home, business and leisure environments. Safely powering home appliances and other electronic devices. Power solution for outdoor parties. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

The generator has a practical double curved handle, to facilitate mobility and storage. It has a completely steel structure and a tank with a maximum capacity of 5 liters. The generator guarantees efficient and silent operation thanks to the engine KOHLER 15440 StageV engine that allows to deliver a maximum power of 5.6KVA.

## STAGEV EMISSIONS REGULATION

With the abbreviation STAGEV, the guidelines and the limits of the gas emissions of the engines are defined. The legislation is respected through the installation of special anti-particulate filters in the generating sets, but an indispensable condition for the filter to work properly is that the generating set works at its design temperature.

## TECHNICAL FEATURES

Type of phase: Single-phase



Continuous use power: 5 KVA / 5 KW  
Maximum power: 5.6 KVA / 5.6 KW  
Motor: KOHLER 15440  
Motor revolutions: 3000 rpm  
Emissions standard: StageV  
Starting: Manual pull  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x Schuko 16A 230V / 1 x 16A 230V CEE  
Tank capacity: 5 l  
Autonomy at 75% of the load: 3.1 h  
Consumption at 75% of the load: 1.6Lt / h  
Length: 780 mm  
Width: 570 mm  
Height: 680 mm  
Dry weight: 85 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brand generators.

Non-binding images and technical data.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 5.6  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 5.6  
Continuous power single phase (KVA): 5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x Schuko 16A 230V / 1 x 16A 230V CEE  
Engine: Kohler KD 15-440  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Pull starter with recoil  
Engine capacity (cm<sup>3</sup>): 436  
Number cylinders: 1  
Cooling: Air  
Alternator: LINZ SP10 MG  
Poles: 2



---

Fuel tank capacity (L): 5  
Consumption (L/h): 1.6 at 75% of the load  
Running time (h): 3.1 at 75% of load  
Length (mm): 780  
Width (mm): 570  
Height (mm): 680  
Dry weight (Kg): 85  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Kohler

