



HYUNDAI HY8000E-1/3 GENERATOR 8,5KW SINGLE-PHASE / THREE- PHASE STAGE V AVR

Product price:

1.145,82 € tax excluded

Product description:

HYUNDAI HY8000E-1/3 GENERATOR 8,5KW SINGLE-PHASE / THREE-PHASE STAGE V AVR

HYUNDAI HY8000E-1/3 is a single/three-phase generator, equipped with a 4-stroke **StageV** petrol-supplied engine, delivering a maximum power of 8,5KW, complete with AVR voltage regulator.

HYUNDAI HY8000E-1/3 is equipped with **electric starter** with battery and a revolutionary **Full Power System**, thanks to which the output power is identical both in single-phase than in three-phase, unlike standard three-phase generators in which the singlephase power is reduced to 1/3.

The HYUNDAI HY8000E-1/3 provides reliable energy for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

The HYUNDAI HY8000E-1/3 has a practical double curved handle, to facilitate mobility and storage. HYUNDAI HY8000E-1/3 has a completely steel structure and a tank with a maximum capacity of 25 liters.

AUTOMATIC TRANSFER SWITCH ATS

The Generator is designed for the use of an ATS automatic transfer switch. Thanks to which you will no longer have to worry about blackouts because in the event of a power failure, this panel is able to start automatically and will allow you to continue your business without losing your work data.



STAGEV EMISSIONS REGULATION

HYUNDAI HY8000E-1/3 is equipped with a "mobile" STAGEV engine, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES HYUNDAI HY8000E-1/3

Phase type: Singlephase / Threephase
Singlephase continuous use output: 7 KVA / 7 KW
Singlephase maximum output: 7.5 KVA / 7.5 KW
Threephase continuous use output: 8 KVA / 8 KW
Threephase maximum output: 8.5 KVA / 8.5 KW
Engine: 4 Strokes
Engine rpm: 3000 rpm
Emissions standard: StageV
Starting: Electric
Fuel: Petrol
Voltage: 230/400 V
Frequency: 50 Hz
Sockets panel: 1 x CEE 16A 230V / 1 x CEE 50A 400V
Tank capacity: 25 l
Acoustic pressure: 88 dB (A) @ 7 m
Length: 710 mm
Width: 550 mm
Height: 580 mm
Dry weight: 86 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or those of other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 7.5
Continuous power single phase (KW): 7
Maximum power single phase (KVA): 7.5
Continuous power single phase (KVA): 7
Maximum power three phase (KW): 8.5

Continuous power three phase (KW): 8
Maximum power three phase (KVA): 8.5
Continuous power three phase (KVA): 8
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x CEE 16A 230V/ 1 x CEE 50A 400V
Engine: 4-stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Alternator: Copper Winding
Fuel tank capacity (L): 25
Acoustic pressure: 88 dB (A) @ 7m
Length (mm): 710
Width (mm): 550
Height (mm): 580
Dry weight (Kg): 86
Silenced: Yes
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR