



GENERATOR SILENCED 110KVA SINGLE- PHASE/THREE-PHASE AUTOMATIC CONTROL PANEL

Product price:

11.970,00 € tax excluded

Product description:

GENERATOR SILENCED 110KVA SINGLE-PHASE/THREE-PHASE AUTOMATIC CONTROL PANEL

The generator single-phase / three-phase is equipped with a Baudouin 4M11G120 / 5 diesel-powered engine, capable of delivering a power of 110KVA complete with **AVR voltage regulator** and automatic control panel.

This generator is equipped with **electric, manual or automatic start** with 12 V battery, and is equipped with **COMAP AMF 9 NT control unit** which allows you to view all electrical parameters of the engine and generator, of the functions, status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

This unit is equipped with a soundproof cabin, made of 20/10 thick carbon steel, folded and electro-welded, with protection class IP23 and which can be opened in two sections. This cabin allows an incredible reduction of noise pollution, up to obtaining an acoustic pressure of only 64 dB (A) recorded at a distance of 7 meters.

The generating set guarantees efficient and silent operation thanks to the Baudouin 4M11G120 / 5 motor, which allows to deliver a maximum power of 110KVA. In addition, this unit is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

AUTOMATIC STARTING PANEL ATS

The generator is set up for the use of an ATS automatic starting panel. Thanks to which you will

no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

The generator control panel consists of:

- Magnetothermic switch 160 A
- Sockets: Terminal block
- Automatic control unit COMAP AMF 9 NT
- Battery charger 2,5 A
- Switching connection
- Emergency stop button

TECHNICAL FEATURES

Phase type: Single-phase / Three-phase

Continuous use power: 100 KVA / 80 KW

Maximum power: 110 KVA / 88 KW

Motor: Baudouin 4M11G120 / 5

Revolutions engine: 1500 rpm

Emissions standard: Not Emitted

Starting: Electric / Automatic

Fuel: Diesel

Voltage available at terminals: 230/400 V

Frequency: 50 Hz

Voltage regulator: AVR

Socket panel: Terminal block

Tank capacity: 140 l

Autonomy at 75% of the load: 8.04 h

Consumption at 75% of the load: 17.4 Lt / h

Acoustic pressure: 64 dB (A) @ 7 m

Length: 2850 mm

Width: 1000 mm

Height: 1420 mm

Dry weight : 1650 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to generating sets of specialized brands.

Non-binding images and technical data.

Product features:



Phase: Single phase / Three phase
Maximum power three phase (KW): 88
Continuous power three phase (KW): 80
Maximum power three phase (KVA): 110
Continuous power three phase (KVA): 100
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Baudouin 4M11G120/5
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric / Automatic
Engine capacity (cm³): 4500
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Alternator: Linz PRO22S D/4
Poles: 4
Fuel tank capacity (L): 140
Consumption (L/h): 17.4 at 75% load
Running time (h): 8.04 at 75% load
Length (mm): 2850
Width (mm): 1000
Height (mm): 1400
Dry weight (Kg): 1650
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR