



EMACH EMI 2000IS GENERATOR 1,8KW SINGLE-PHASE INVERTER STAGE V

Product price:

565,00 € tax excluded

Product description:

EMACH EMI 2000IS GENERATOR 1,8KW SINGLE-PHASE INVERTER STAGEV

EMACH EMI 2000IS single-phase generator is gilded with a R80I StageV petrol-powered engine, capable of delivering a maximum power of 1.8KW, super quiet thanks to the supplied inverter.

EMACH EMI 2000IS is small in size and thanks to the handle integrated into the body, they make the generator perfect for transport and easy placement during periods of inactivity. All the materials used for the manufacture of the groups of the EMACH EMI 2000IS, are of first choice, offering and guaranteeing the customer a tested and tested product at a truly affordable price.

Thanks to the electrical stabilizer of the Inverter technology that works with very low distortion, the generator delivers constant current loads without voltage peaks that could damage electrical and electronic devices. Another advantage of the inverter is to work with variable motor revolutions, based on the need for current to be supplied, optimizing fuel consumption, gas emission and wear of the mechanical parts. Ideal product for use in campsites, campers and for outdoor leisure.

STAGEV EMISSIONS REGULATION

The EMACH EMI 2000IS is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics of EMACH EMI 2000IS



Type of phase: Single-phase
Continuous power: 1.6 KVA / 1.6 KW
Maximum power: 1.8 KVA / 1.8 KW
VAC voltage: 230 V
Frequency (Hz): 50
Voltage regulator: INVERTER
Starting panel: Manual pull
Engine: R80I 4-stroke
Emissions standard: Stage V
Revolutions per minute RPM: Variable
Power supply: Petrol
Sockets panel: 1 x shuko 16 A
Tank capacity: 4.2 l
Autonomy: 3.5 h
Consumption: 1.2 l / h
Acoustic pressure : 68 dB (A) @ 7 m
Length: 510 mm
Width: 300 mm
Height: 475 mm
Net weight: 23.5 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to EMACH generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 1.8
Continuous power single phase (KW): 1.6
Maximum power single phase (KVA): 1.8
Continuous power single phase (KVA): 1.6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A SCHUKO
Engine: R80I 4-stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): Variable
Speed governor: Electronic
Ignition: Recoil
Starting system: Pull starter



Cooling: Air

Fuel tank capacity (L): 4.2

Consumption (L/h): 1.2

Running time (h): 3.5

Acoustic pressure: 68 dB(A) at 7 m

Length (mm):

Width (mm): 300

Height (mm): 475

Dry weight (Kg): 23.5

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: Inverter

