



PTO Generator Single Phase 18 kVA/ Three Phase 45 kVA AVR

Product price:

3.392,00 € tax excluded

Product description:

PTO Generator Single Phase 18 kVA/ Three Phase 45 kVA AVR

- For outdoor applications (field and home), in case of blackouts and in areas not served by the power grid
- Supplied with multiplier kit and protection, support with 3-point attachment (patented design), electrical panel with multifunction digital display for real-time data reading (voltmeter, frequency meter, ammeter, hour meter)
- Durability over time and maximum protection (thermal-magnetic and differential)
- Warranty 12 months
- Easy packaging and storage

Technical Features

Phase: Single / Three Phase

RPM: 1500

Required tractor power (Hp): 124

Single-phase power (kVA): 18

Three-phase power (kVA): 45

Pto Speed (rpm): 430

Voltage (V): 230 / 400

Frequency (Hz): 50

Length (mm): 1135

Width (mm): 640

Height (mm): 915

Weight (Kg): 258

AVR



Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 14.4

Maximum power single phase (KVA): 18

Maximum power three phase (KW): 36

Maximum power three phase (KVA): 45

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V SCHUKO

Engine rpm (rpm): 1500

Protection degree: IP23

PTO speed (round/min): 430

Minimum tractor output (HP): 124

Transmission ratio: 1 : 3.5

Length (mm): 1135

Width (mm): 640

Height (mm): 915

Dry weight (Kg): 258

Brushes: No

Voltage regulator: AVR