



MENNEKES COMBINATION OF SOCKETS AMAXX 931392

Product price:

400,00 € tax excluded

Product description:

MENNEKES COMBINATION OF AMAXX 931392 SOCKETS

MENNEKES AMAXX 931392 is a combination of 6 16A CEE 230 V single-phase sockets, in a single panel, easy to assemble and use, equipped with magnetothermic and differential protection.

Thanks to the MENNEKES AMAXX 931392 switchgear you can cleverly mount and save valuable assembly time in any work environment, thanks to the IP 44 protection class.

Just one power line, means fewer holes, fewer cables and zip ties, and one housing, making it easier for you to manage the logistics of power distribution on job sites. Each switchgear socket is equipped with magnetothermic protection to prevent the risk of fire, and differential protection, for total disconnection of the mains in the event of a short circuit, giving you total safety on the system.

The external mounting allows installation by a single operator, thanks to the combination cover that can be opened laterally as well as the sliding profile rails and the large connection space that facilitate wiring. MENNEKES AMAXX 931392 is ready for connection to the mains and tested for safety and quality according to IEC 61439.

TECHNICAL CHARACTERISTICS MENNEKES AMAXX 931392

N.6 CEE 16 A, 3 P, 230 V

Protection: N.1 RCCB 40A, 4P, 0.03A / N.6 Circuit breaker 16A, 1P + N, C

Connection options / Power cable: 1.5 m H07RN-F5G4 with 32 A plug, 5 p, 400 V

Degree of protection: IP 44

Material: plastic casing in RAL 7035 color





Safety lock: Phase
Length: 165 mm
Width: 225 mm
Height: 390 mm
Weight: 5.5 Kg

Are you looking for a product with different characteristics? HERE you can find the entire range of accessories for MENNEKES generators or other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Sockets configuration: 6 x CEE 16 A, 3 P, 230 V
Protection degree: IP44
Material: Plastic
Length (mm): 165
Width (mm): 225
Height (mm): 390
Product type: Socket box
Fusing: 1 x RCD 40A, 4P, 0.03A - 6 x MCB's 16A, 1P+N, C
Pre-fuse max. (A): 40
Connection / Feeder cable: 1 m H07RN-F5G4 with CEE-plug 32 A, 5P, 400 V
Weight (Kg): 5.5

