



PRAMAC GBW10P SINGLE/THREE-PHASE GENERATOR 9.65 KVA SOUNDPROOF WITH MANUAL PANEL



Product price:

8.988,75 € tax excluded

Product description:

Generator PRAMAC GBW10P MCP Three-phase 9.65 KVA Supersilenced

The PRAMAC GBW10P single-phase / three-phase generator set is equipped with a Perkins 403D-11G **Diesel powered** engine, capable of delivering a power of 9.65KVA complete with **compound voltage regulator**.

The PRAMAC GBW10P generating set is equipped with an electric start with manual control unit that allows you to view all the electrical parameters of the engine and generator, the functions, the status of the generating set, manage the entire set and view, if system errors or warnings.

PRAMAC GBW10P is equipped with a soundproof cabin, made of galvanized, folded and electro-welded sheet metal, with protection class IP23 with doors that can be opened for ordinary and extraordinary maintenance. The generating set guarantees efficient and silent operation thanks to the Perkins 403D-11G Diesel engine, which allows to deliver a maximum power of 9.65 KVA.

Technical characteristics PRAMAC GBW10P MCP:

Phase type: Single-phase / Three-phase
Continuous use power: 8.71 KVA / 6.97 KW
Maximum power: 9.65 KVA / 7.72 KW
Motor: Perkins 403D-11G
Revs engine: 1500 rpm
Emissions standard: Not Emitted
Starting: Electric



Fuel: Diesel
Voltage available at terminals: 230/400 V
Frequency: 50 Hz
Voltage regulator: Compound
Tank capacity: 50 l
Consumption at 75% load: 1.98 l / h
Autonomy at 75% load: 25.76 h
Acoustic pressure: 66 dB (A) @ 7 m
Length: 1645 mm
Width: 870 mm
Height: 1072 mm
Dry weight: 460 Kg

Sockets:

N.1 3P + N + T CEE 400V 32A
N.1 3P + N + T CEE 400V 16A
N.2 2P + T CEE 230V 16A
N.1 230V 16A SCHUKO

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to PRAMAC generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Three phase
Maximum power three phase (KW): 7.72
Continuous power three phase (KW): 6.97
Maximum power three phase (KVA): 9.65
Continuous power three phase (KVA): 8.71
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine: Perkins 403D-11G
Emissions Regulations: Not Emitted
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 1131
Number cylinders: 3
Cylinders' position: In line

Oil capacity (L): 4.9

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 50

Consumption (L/h): 1.9 at 75% of the load

Running time (h): 25 at 75% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 460

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Perkins