



GENERATOR SINGLE-PHASE 9,7KVA SILENT ELECTRIC START

Product price:

7.290,00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE 9,7KVA ELECTRIC START

The generator single-phase, is equipped with a KOHLER 425-2 Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

It is equipped with electric start and has a low fuel consumption, in fact it consumes only 2,5 liters/hour at 75% of the load for an autonomy of up to 8 hours of operation.

The generator is equipped with silenced casing that can be opened in two sections made of sheet 20/10, soundproofing material in class 1, internal muffler. Thanks to these devices, the generator can be considered super-silenced, with a noise emission of only 75 dB recorded at a distance of 7 meters from the source.

The generator guarantees efficient and silent operation thanks to the KOHLER KD 15440 engine, which allows to deliver a maximum power of 9.7KVA.

ATS AUTOMATIC STARTING FRAME

The generator is designed for use with an ATS automatic start-up panel. Thanks to this, you will no longer have to worry about blackouts, in the event of a power failure this panel is able to automatically turn on the generator and allow you to continue your business.

The generator control panel consists of:

- Thermomagnetic circuit breaker and isolation control
- Sockets: 1 x 16A 3P 230V / 1 x 32A 3P 230V
- ATS arrangement
- Voltmeter
- Ammeter



- Hour meter
- Ignition switch
- Emergency stop button

TECHNICAL FEATURES

Phase Type: Single Phase
Continuous Use output: 8.8 KVA / 8.8 KW
Maximum output: 9.7 KVA / 9.7 KW
Motor: KOHLER 425-2
Motor Speed: 3000 rpm
Emissions Standard: NOT Emitted
Boosting: Electric
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket Frame: 1 x 16A 3P 230V / 1 x 32A 3P 230V
Tank Capacity: 20 l
Autonomy at 75% of load: 8 h
Consumption at 75% of load: 2.5 Lt/h
Acoustic pressure: 75 dB(A) @ 7 m
Length: 940 mm
Width: 650 mm
Height: 840 mm
Dry weight: 235 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 9.7
Continuous power single phase (KW): 8.8
Maximum power single phase (KVA): 9.7
Continuous power single phase (KVA): 8.8
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 16A 3P 230V / 1 x 32A 3P 230V
Engine: Kohler KD 425/2

Emissions Regulations: Stationary Use
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 954
Number cylinders: 2
Cooling: Air
Alternator: LINZ E1C11MB
Poles: 2
Fuel tank capacity (L): 20
Consumption (L/h): 2.5 at 75% of the load
Running time (h): 8 at 75% load
Acoustic pressure: 75 dB(A) at 7 m
Length (mm): 940
Width (mm): 650
Height (mm): 840
Dry weight (Kg): 235
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler