



GENSET MG 4000 I-BE GENERATOR 3,8 KVA SINGLE PHASE STAGE V

Product price:

673,00 € tax excluded

Product description:

GENSET MG 4000 I-BE GENERATOR 3,8 KVA SINGLE PHASE STAGEV

The GENSET MG 4000 I-BE single-phase generator is equipped with a Briggs & Stratton XR950 StageV petrol-powered engine capable of delivering a power of 3,8 KVA with **capacitor voltage regulator**.

The GENSET MG 4000 I-BE single-phase generator provides reliable power for home, business and leisure environments Safely powering home appliances and other electronic devices Outdoor party power solution.

The generator is easy to install and operate, just as simple are starting and stopping thanks to the clear and intuitive controls (recoil start).

The GENSET MG 4000 I-BE, is equipped with sturdy handles that allow easy portability; like the entire GENSET MG range, it is a genset that meets a high standard of quality and ensures a high level of reliability.

STAGEV EMISSIONS REGULATION

GENSET MG 4000 I-BE is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES GENSET MG 4000 I-BE

Type of phase: Single phase

Maximum power: 3.85 KVA / 3 KW



Continuous power: 3.5 KVA / 2.8 KW
VAC voltage: 230 V
Frequency (Hz): 50
Starting panel: Manual
Engine: Briggs & Stratton XR950
Emissions standard: StageV
Revolutions per minute RPM: 3000
Fuel: Petrol
Tank capacity: 3.1 l
Consumption @ 75% load: 1.7 l / h
Autonomy @ 75% load: 1.8 h
Acoustic pressure: 72 dB (A) @ 7m
Length: 610 mm
Width: 360 mm
Height: 410 mm
Net weight: 40 Kg

Are you looking for a generator with different characteristics? [HERE](#) you can find the full range of GENSET generators or other specialized brands

Non-binding images and technical data.

Product features:

Phase: Single phase
Maximum power single phase (KW): 3
Continuous power single phase (KW): 2.8
Maximum power single phase (KVA): 3.85
Continuous power single phase (KVA): 3.5
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 Schuko
Engine: Briggs & Stratton XR950
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Manual
Engine capacity (cm³): 208
Number cylinders: 1
Cooling: Air
Protection degree: IP23
Motor insulation class: H



Fuel tank capacity (L): 3.1
Consumption (L/h): 1.7 at 75% load
Running time (h): 1.8 at 75% load
Acoustic power: 97 dB(A)
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 610
Width (mm): 360
Height (mm): 410
Dry weight (Kg): 40
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor
Engine manufacturer: Briggs&Stratton

