

GENERATOR 4 KW SUPER SILENT INVERTER STAGEV



Product description:

GENERATOR 4 KW SUPER SILENT INVERTER STAGEV

Generator, equipped with a gasoline-powered GENKINS OHV 225 **StageV** engine, delivers a maximum power of 4KW, complete with **Inverter voltage regulator**.

Even more silent and efficient than traditional models, the generating set delivers a stable and precise single-phase power of 4KW suitable for powering sophisticated electronic equipment sensitive to voltage and frequency variations.

It is therefore possible to enjoy quietly and easily of all the small comforts of home wherever you are: lights, fans, a coffee machine, laptops, radio or TV.

The compact size and low weight make the generator extremely manageable and easy to transport thanks to the towing trolley with integrated wheels and removable telescopic handle, this makes it extremely versatile.

The 12 Lt tank allows for a continuous operation of more than 8 hours.

The safety of use is guaranteed by the overload protection and engine shutdown due to low oil level.

The Generator can also be used in parallel, i.e. it can be connected to another identical generator in order to deliver double the power and increase efficiency.

The generator is also equipped with two 230 V (16 A) domestic voltage sockets, two USB ports and a 12 V (5 A) battery charging socket that allow you to power lights, radios, TVs, small appliances, laptops and tablets, mobile phones and much more.

STAGEV EMISSIONS REGULATION

Equipped with "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of

particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics:

Phase type: Single phase
Continuous use power: 4 KVA / 4 KW
Maximum power 3.6 KVA / 3.6 KW
Motor: GENKINS 225 230M
Revs : Variable 3600 rpm
Emissions standard: StageV
Starting: Recoil with wrap-around car
Fuel: Petrol
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 2 x schuko 16A 230 V
Tank capacity: 12 l
Consumption at 75% of the load: 1.4 l / h
Autonomy: 8.5 h
Acoustic pressure: 66.8 dB (A) @ 7 m
Voltage regulator: Inverter
Length: 605 mm
Width: 432 mm
Height: 500 mm
Net weight: 42 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brand generators.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 4
Continuous power single phase (KW): 3.6
Maximum power single phase (KVA): 4
Continuous power single phase (KVA): 3.6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 x 230V 16A 2P+T SCHUKO

Engine: GK 225
Emissions Regulations: Stage 5
Engine rpm (rpm): 3600
Starting system: Manual / Electric
Engine capacity (cm³): 223
Number cylinders: 1
Alternator: Permanent magnets, self-excited, brushless
Fuel tank capacity (L): 12
Consumption (L/h): 1.4
Running time (h): 8.5
Acoustic power: 92 dB(A)
Acoustic pressure: 66 dB(A) at 7 m
Length (mm): 605
Width (mm): 432
Height (mm): 500
Dry weight (Kg): 42
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Inverter