



# CUMMINS C66D5EQ GENERATOR 66KVA SING LE-PHASE/THREE-PHASE OPEN

Product price:

**12.154,00 € tax excluded**

## Product description:

CUMMINS C66D5EQ GENERATOR 66KVA SINGLE-PHASE/THREE-PHASE OPEN

The CUMMINS C66D5EQ generator is equipped with a Cummins 4BTAA3,3-G14 engine powered by diesel and is capable of delivering a maximum power of 66KVA, complete with compound voltage regulator.

The CUMMINS C66D5EQ is equipped with **PowerStart 600** control unit which allows you to view all the electrical parameters of the engine and generator, the functions, the status of the generating set, manage the entire group and view, in case they occur, system errors or alarms. Controller provides simple interface, auto/manual and remote start/stop control and stop fault indication. The integration of all control functions in a single command ensures greater reliability and performance compared to conventional generator set control systems.

The Generator is equipped with an electric start and with low fuel consumption, in fact it consumes about 11 litres/hour at 75% of the load for an autonomy of up to 18 hours of operation. The generator set guarantees efficient and silent operation thanks to the Cummins 4BTAA3,3-G14 engine, which allows it to deliver a maximum power of 66KVA.

In addition, it is equipped with automatic starting via the ATS panel, which allows it to be switched on autonomous in case of blackout.

Thanks to the advanced control unit, the generator is equipped with:

PC based software service tool

Inpower Modbus interface for interconnection with PLC/BMS

Configurable inputs and outputs

Configurable alarm inputs to cause a shutdown or warning response

## ATS AUTOMATIC STARTER PANEL ARRANGEMENT

The CUMMINS C66D5EQ generator is designed for connection to ATS automatic starter panel. Thanks to which you will no longer have to worry about blackouts, since, in the event of a power failure from the mains, this panel is able to turn on the group and will allow you to continue your business without losing your work data.

## CUMMINS C66D5EQ TECHNICAL SPECIFICATIONS

Phase type: Single-phase / Three-phase  
Continuous power: 60 KVA / 48 KW  
Maximum power: 66 KVA / 53 KW  
Engine: Cummins 4BTAA3,3-G14  
Fuel system: Diesel  
Engine speed: 1500 rpm  
Regulation of revolutions: Mechanical  
Alternator: Stamford UC224F  
Emissions standard: Stage III A  
Starter: Electric / Automatic  
Voltage regulator: Compound  
Voltage: 230/400 V  
Frequency: 50 Hz  
Socket panel: Terminal box  
Tank capacity: 200 l  
Consumption at 75% load capacity: 11.11 l/h  
Autonomy at 75% load: 18 h  
Length: 2315 mm  
Width: 1015 mm  
Height: 1480 mm  
Weight a dry: 1016 kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of CUMMINS generators and other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

### Product features:

Phase: Single phase / Three phase  
Maximum power three phase (KW): 53  
Continuous power three phase (KW): 48  
Maximum power three phase (KVA): 66

---

Continuous power three phase (KVA): 60  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Cummins 4BTAA3.3-G14  
Emissions Regulations: Stage 3A  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric Automatic/Manual  
Number cylinders: 4  
Cylinders' position: In line  
Alternator: Synchronous, brushless  
Poles: 4  
Fuel tank capacity (L): 200  
Consumption (L/h): 11.11 at 75% load  
Running time (h): 18 at 75% load  
Length (mm): 2315  
Width (mm): 1015  
Height (mm): 1480  
Dry weight (Kg): 1016  
Silenced: No  
Super silenced: No  
Brushes: No  
Product type: Generator  
Control unit: PowerStart 600  
ATS Switch device : Optional  
Type of alternator: Constant Speed  
Voltage regulator: Compound  
Engine manufacturer: Cummins  
Precision of voltage regulation: 0.5%