



VISA BD 20 CK GENERATOR 22KVA SILENCED SINGLE- PHASE/THREE-PHASE AVR

Product price:

7.458,00 € tax excluded

Product description:

VISA BD 20 CK GENERATOR 22KVA SILENCED SINGLE-PHASE/THREE-PHASE AVR

The VISA BD 20 CK single-phase/three-phase generator is equipped with a BAUDOIN 4M06G25/5 diesel engine, capable of delivering a maximum power of 22KVA, complete with **AVR voltage regulator**.

The VISA BD 20 CK generator is compact and easy to use, equipped with a bonnet with sound-absorbing panels that significantly lower acoustic emissions and make it **supersilenced**.

The generator consists of a STAMFORD S0L2-G alternator with AVR voltage regulator which also allows it to be used with equipment sensitive to current surges.

The AVR is a device that allows **to keep the output more constant and less dependent on the load**. Thanks to this card, there are fewer current drops or peaks and this makes the use of the various connected devices safer, improving their performance and duration.

The Generator is equipped with electric start and with low fuel consumption, in fact it consumes only 4.5 litres/hour at 75% of the load for an autonomy of up to 20 hours of operation. In addition it is equipped with automatic starting via the ATS panel, which allows it to be switched on independently in the event of a blackout.

ATS AUTOMATIC START PANEL

The VISA BD 20 CK generator is designed for connection to ATS automatic starter panel. Thanks to which you will no longer have to worry about blackouts, since, in the event of a power failure

from the mains, this panel is able to turn on the group and will allow you to continue your business without losing your work data.

TECHNICAL FEATURES OF VISA BD 20 CK:

Phase type: Single-phase/Three-phase

Continuous power: 20 KVA / 16 KW

Maximum power: 22 KVA / 17.6 KW

Motor: BAUDOUIN 4M06G25/5

Power supply: Diesel

Engine speed: 1500 rpm

Regulation of revolutions: Mechanical

Alternator: STAMFORD S0L2-G

Emissions standard: Not Emissions

Starter: Electric / Automatic

Regulator voltage: AVR

Voltage: 230/400 V

Frequency: 50 Hz

Socket panel: Terminal block

Tank capacity: 90 l

Consumption at 75% of the load: 4.5 l/h

Autonomy at 75% load: 20 h

Acoustic pressure: 70 dB(A) at 7 m

Length: 2100 mm

Width: 930 mm

Height: 1280 mm

Net Weight: 720 mm

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the whole range of VISA generators and other specialized brands.

Non-binding images and technical data

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 17.6

Continuous power three phase (KW): 16

Maximum power three phase (KVA): 22

Continuous power three phase (KVA): 20

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Terminal box
Engine: BAUDOUIN 4M06G25/5
Emissions Regulations: Not Emitted
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric / Automatic
Cooling: Water
Alternator: STAMFORD S0L2-G
Poles: 4
Fuel tank capacity (L): 90
Consumption (L/h): 4.5 at 75% load
Running time (h): 20 at 75% of the load
Length (mm): 2100
Width (mm): 930
Height (mm): 1280
Dry weight (Kg): 720
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Baudouin