



MASTERVOLT CHARGEMASTER PLUS 24/80-2

Product price:

1.699,00 € tax excluded

Product description:

ChargeMaster Plus 24/110-2

All-in-one solution for faster and safer charging

ChargeMaster Plus is the next generation of battery chargers that integrates multiple functions into one single device. Replacing auxiliary chargers, battery isolators and VSR, ChargeMaster Plus reduces system complexity and cost. Designed for versatility, it charges virtually any combination of two batteries in a fast and safe way and works anywhere in the world.

With the new Battery's Best Friend architecture, ChargeMaster Plus is capable of charging a multitude of battery chemistries, sizes and voltages. All batteries are charged with the fast and safe 3-step+ charge method. Other unique features are:

Revival mode: automatically revives even fully depleted batteries.

Multi voltage: charge 12 V starter battery in a 24 V system, without additional components.

Priority Charge: redirect available power to the lowest battery, for faster charging.

Global Charging

The ChargeMaster Plus handles worldwide AC voltages and frequencies. Resisting large voltage fluctuations and high temperatures, it keeps working in harsh environments. For marine and mobile markets, the ChargeMaster Plus is CE, ABYC, UL, SAE, CEC/DOE and RCM/C-Tick compliant.





System Simplicity

Nowadays, equipment must be self-explaining. The ChargeMaster Plus displays the charge phase of all outputs in an understandable way. Robust and ergonomic connections save installation time.

Powerful Communications thanks to CZone integration

In modern applications, all electrical components work together. The CAN-based MasterBus enables the ChargeMaster Plus to communicate with displays, shunts and power systems including communication standards like CZone®, NMEA 2000 and CANopen (through additional interfaces).

Models with the addition CZone do not only support MasterBus, but also support CZone and NMEA 2000 communication, without the need of additional interfaces. This ChargeMasters Plus series can be configured via MasterBus or will accept a CZone configuration file just like any other CZone device. Other communication standards like ModBus, CANopen, LinBus, etc. are supported via additional interfaces.

This wide range of communication interfaces makes the ChargeMaster Plus ideally suited for system integration. In addition, the ChargeMaster Plus can operate as a power supply for delicate communication equipment, or during the construction phase of a boat.

Features

Multicharger with two outputs, DC-DC converter and current limiter.

Combine Lithium Ion, Gel or AGM, and large or small battery banks on a single battery charger.

Extended specifications: offers 20 % more output at 14.4 V and 80 % charging power at 60 °C.

Safe Charge: quickly recognize the State of Charge for extended battery life.

Very wide operating range of 80-275 V AC, 35-70 Hz.

Compact, easy to connect and quick to install.

Not binding images and technical data.



Product features:

Frequency (Hz): 50 / 60

Cooling: Vario fan

Protection degree: IP23

Length (mm):

Width (mm): 250

Height (mm):

Nominal output voltage (V): 24

Total charge current: 80 A at 28.8 V

Number of battery outlets:

Battery capacity range (Ah):

Nominal input voltage (V): 120/230 (90-265)

AC connection: Connector strips

Power supply mode: Yes

Display/read-out: LED display

Fastening: Mounting bracket (included) or 4x screw

Approvals: CE, ABYC A-31, SAE J1171/ISO 8846 ignition protected, RMRS, RRR

Charge characteristic: IUoUo, automatic 3-stage+ for Gel/AGM/liquid lead/Lithium-ion + user-defined option

Charge voltage Absorption (V): 28.5

Temperature compensation: Yes

DC voltage compensation: Automatic

Power consumption (DC side) (mA): Less than 5

Current Control function: Yes, through MasterBus

Power factor control: ? 0.98

Temperature range (ambient temp.): -25 °C at 80 °C, reduction greater than 45 °C -13 °F at 176 °F

Protections: Over temperature, over load, short circuit, high/low battery voltage

MasterBus compatible: Yes

Weight (Kg):