



# GENERATOR 9KVA SINGLE PHASE / THREE PHASE STAGEV AVR

Product price:

**1.230,00 € tax excluded**

## Product description:

### GENERATOR 9KVA SINGLE PHASE / THREE PHASE STAGEV AVR WITH ATS

Generator Single-phase / three-phase with STAGEV petrol-powered engine at 3000 rpm, capable of delivering a maximum power of 9 KVA, with transport trolley as standard equipment, complete with AVR voltage regulator.

The generator is characterized by lower consumption and a longer life expectancy than the petrol-powered range. The generator consists of a self-excited alternator with brushes and voltage regulator **AVR**. The generator has low fuel consumption, in fact it consumes only 2.1 litres/hour at 75% of the load for an autonomy of more than 12 hours of operation.

### STAGEV EMISSION REGULATIONS

The generator set is equipped with a "mobile" STAGEV engine, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions released by the generator into the environment, and guarantee a 200% reduction in environmental impact compared to standard engines.

### AVR VOLTAGE REGULATOR

Its operation is very simple when resistive loads are powered, the situation is more complex in the case of predominantly inductive loads: the delayed phase-shifted current contrasts the inductor magnetic field, causing a drop in voltage at the output terminals of the alternator; to compensate the phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value. If the load is instead capacitive, the current acts as a magnet for the inductor causing an increase in the output voltage, and the AVR intervenes by reducing the excitation current.

### ATS AUTOMATIC STARTER PANEL ARRANGEMENT



The generator set includes an ATS automatic transfer switch. Thanks to which you will no longer have to worry about blackouts because if the electricity goes off, this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

#### TECHNICAL FEATURES:

Phase type: Single-phase / Three-phase

Continuous use Single-phase: 2.7 KVA / 2.2 KW

Maximum power Single-phase: 3 KVA / 2.4 KW

Continuous use Three-phase: 8.2 KVA / 6.6 KW

Maximum three-phase power: 9 KVA / 7.2 KW

Fuel: Petrol

Voltage: 400 / 230 V

Frequency: 50 Hz

Motor: 16 HP

Revolutions engine: 3000 rpm

Emissions standard: StageV

Starter: Electric

Voltage regulator: AVR

Consumption: 2.1 Lt/h at 75% load

Capacity tank: 25 Lt

Autonomy: 11.9 h at 75% of the load

Acoustic pressure: 70 dBA @ 7m

Socket panel: 1 x schuko 230V | 1 x CEE 16A 5P 400V socket | 1 x 12VDC socket

Length: 725 mm

Width: 600 mm

Height: 620 mm

Weight: 87 Kg

You are looking for a product with technical characteristics different? [HERE](#) you can find the area dedicated to specialized brands.

The images and technical data are not binding, the color of the group may vary based on availability.

#### Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.4

Maximum power single phase (KVA): 3

Maximum power three phase (KW): 7.2

Maximum power three phase (KVA): 9

---

Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V - 1 x 230V  
Engine: 16 HP  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Manual / Electric  
Engine capacity (cm<sup>3</sup>): 460  
Number cylinders: 1  
Alternator: Copper  
Fuel tank capacity (L): 25  
Consumption (L/h): 2.1  
Running time (h): 11.9  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 725  
Width (mm): 600  
Height (mm): 620  
Dry weight (Kg): 87  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : Yes  
Voltage regulator: AVR