



MOSA GE 50 KR-5 GENERATOR 50 KVA SIN GLE-PHASE/THREE-PHASE AVR STAGE V

Product price:

22.972,12 € tax excluded

Product description:

MOSA GE 50 KR-5 GENERATOR 50 KVA SINGLE-PHASE/THREE-PHASE AVR STAGE V

The MOSA GE 50 KR-5 single-phase/ three-phase equipped with a diesel-powered KOHLER KDI 2504TCR StageV capable of delivering a maximum power of 50 KVA, complete with **AVR voltage regulator**.

The MOSA GE 50 KR-5 generator set is the perfect choice for you. equipped with **electric**, **manual or automatic start** with 12 V battery, and is; equipped with **IntiLite AMF 9** control unit which allows you to view all the electrical parameters of the engine and generator, the functions, the status of the generating set, manage the entire group and view, if any , errors or system alarms.

Thanks to the AVR voltage regulator included in the supply of the group, the MOSA GE 50 KR-5 manages to supply "clean" current and voltage with an accuracy of less than one percent, this guarantees the user to be able to connect safely any type of electrical and electronic device.

The GENERATOR MOSA GE 50 KR-5 guarantees efficient and silent operation thanks to the KOHLER KDI 2504TCR engine, which allows to deliver a maximum power of 50 KVA.

ATS AUTOMATIC STARTER PANEL (OPTIONAL)

The generator set is ready for use. prearranged for the use of automatic starting panel ATS. Thanks to which you will no longer have to; worry about blackouts because if it goes via the mains, this panel is on. capable of starting the generator automatically and will allow you to to continue your business; without losing your work data.

STAGEV EMISSION REGULATIONS





The generator set is ready for use. equipped with a "mobile" STAGEV engine, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides supplied by the generator into the environment, and guarantee a 200% reduction in environmental impact compared to standard engines.

TECHNICAL SPECIFICATIONS GE 50 KR-5

Phase type: Single-phase / Three-phase

Maximum power: 50 KVA / 40 KW Continuous power: 45 KVA / 36 KW

Fuel: Diesel

Voltage: 230 / 400 V Frequency: 50 Hz

Engine: KOHLER KDI 2504TCR Emissions standard: Stage V

Number of cylinders: 4 Engine speed: 1500 rpm

Starter: Electric

Voltage regulator: AVR HVR-30 Capacity & agrave; tank: 245 Lt

Consumption: 8.4 Lt/h at 75% of the load

Autonomy: 29 h at 75% of the load Acoustic pressure: 67 dB(A) @ 7m

Length: 2401 mm Width: 1100 mm Height: 1575 mm Net weight: 1270 Kg

Are you looking for a generator set with different technical characteristics? HERE you can find the area dedicated to MOSA generator sets or other specialized brands.

The images are purely indicative.

Product features:

Phase: Single phase / Three phase Maximum power three phase (KW): 40 Continuous power three phase (KW): Maximum power three phase (KVA): 50 Continuous power three phase (KVA): 36

Fuel: Diesel

Frequency (Hz): 50





Voltage (V): 230 / 400

Sockets configuration: 1x 400V 63A 3P+N+T CEE- 1x 400V 32A 3P+N+T CEE- 1x 400V 16A

3P+N+T CEE - 1x 230V 16A 2P+T CEE - 1x 230V 16A 2P+T SCHUKO

Engine: KOHLER KDI 2504TCR Emissions Regulations: Stage 5

Engine rpm (rpm):

Speed governor: Electronic Starting system: Electric Engine capacity (cm³): 2482

Number cylinders: 4 Cooling: Water Inyección : Direct

Alternator: LINZ – PRO18L F/4 Fuel tank capacity (L): 245

Consumption (L/h): 8.4 at 75% of the load Running time (h): 29 at 75% of the load

Acoustic power: 92 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2401 Width (mm): 1100 Height (mm): 1575 Dry weight (Kg): 1270

ATS Switch device: Optional

Voltage regulator: AVR

Engine manufacturer: Kohler