



# UNIMEC MINITRANSPORTER FG3306 CAPACITY 600 KG HYDRAULIC TIPPING

**Product price:**

**5.865,00 € tax excluded**

## **Product description:**

UNIMEC MINITRANSPORTER FG3306 CAPACITY 600 KG HYDRAULIC TIPPING

UNIMEC MINITRANSPORTER FG3306 is a mini transporter equipped with a Honda GX200 gasoline-powered engine with a load capacity of up to 600Kg and hydraulic tipping system.

UNIMEC FG3306 is ideal for transporting goods and materials in confined spaces and difficult access. Its solid and sturdy construction makes it suitable for use in various environments such as construction sites, gardens, agricultural facilities, parks and parking lots.

The Unimec FG3306 mini transporter is equipped with a 196cc single-cylinder four-stroke gasoline engine, which provides enough power to pull the transporter even over difficult terrain. The conveyor has a maximum load capacity of 600 kg in the skip. The body is made of corrosion- and weather-resistant sheet steel. The structure is designed to ensure load stability and operator safety.

Unimec FG3306 is equipped with rubber tracks that provide good grip on various terrains, both paved and unpaved. UNIMEC MINITRANSPORTER FG3306 reliable, robust, provides good transport efficiency in harsh environments. Its compact design, loading capacity and versatility make it suitable for many tasks, from handling materials inside buildings or construction sites to handling light equipment and products in parks and gardens.

The mini conveyor is equipped with over-center valves designed to provide precise control of hydraulic cylinder movement, minimizing the risk of accidental load drops. The blocking action of the valve occurs when the cylinder piston exceeds the equilibrium point and the load moment is greater than the resistance moment. The over center valve regulates the flow of oil in and out of the cylinder, allowing precise control of the movement and preventing the risk of sudden load drop.



---

**TECHNICAL FEATURES UNIMEC MINITRANSPORTER FG3306**

Engine: Honda GX200

Power: 6 Hp

Power supply: Petrol

Starter: Recoil, Self rewinding

Speed: maximum speed: 2.4 km/h

Transmission: Hydraulics with gear pump

Hydraulic pumps: PLP 10-4 2 UNITS

Cylind. mot. hydraulics: 2 units 4 cc/rev (5.82 Lt at 1500 revs)

Maximum pressure: 130 bar

Hydraulic oil tank: 16 l

Construction skip capacity: 600 Kg

Tipping: Hydraulic

Safety system: Overcenter

Maximum gradient allowed: 46%

Rubber tracks: 180 x 34 x 72 mm

Width: 1584 mm

Depth: 700 mm

Height: 1140 mm

Building box weight: 55 Kg

Net weight: 300 kg

Are you looking for a tracked forklift with different technical characteristics? [HERE](#) you can find the whole range of tracked trolleys by UNIMEC or other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer .

**Product features:**

Fuel: Gasoline

Engine: Honda GX200

Engine rpm (rpm): 1500

Length (mm): 1584

Width (mm): 700

Height (mm): 1140

Dry weight (Kg): 300

Capacità di carico in piano (Kg): 600