



BIEMMEDUE SUPER 200/21 DIESEL HYDROCLEANER FLOW RATE 1260 l/h

Product price:

3.723,45 € tax excluded

Product description:

BIEMMEDUE SUPER 200/21 DIESEL HYDROCLEANER FLOW RATE 1260 l/h

BIEMMEDUE SUPER 200/21 is a pressure washer with a Diesel engine dedicated to professional and industrial cleaning capable of delivering both hot and cold water at a pressure of 200 bar.

With a maximum pressure of 200 bar and a water flow of 1260 liters per hour, it can remove dirt and stains from even the most difficult surfaces.

The machine is equipped with a Diesel engine that allows it to be used anywhere without the need for an electrical outlet. It also has a detergent tank, which allows the cleaner to be applied precisely and evenly.

The Biemmedue Super 200/21 pressure washer is designed for long life and great reliability. The machine also has a number of safety features, including a water shortage protection system and an automatic shut-off system in case of overload. The gun is equipped with a safety locking device, which prevents accidental release of pressure.

The Biemmedue Super 200/21 pressure washer is easy to use, thanks to its sturdy wheels that make it easy to move around. It also has an easy starting system and an ergonomic handle, making it comfortable to use even for prolonged periods.

STANDARD EQUIPMENT INCLUDED WITH THE SUPPLY

Water gun with semi-lance (in M22 out M22)

STEEL lance l=70 cm (in M22 out 1/4" F)

Nozzle 1/4" M 25065



H.P. -H.P. Hose l=10 m R2 - 5/16" M22 - M22
1/2" quick coupling hose connector
3/4" hose connector
1 l of anti-limescale additive
Key

TECHNICAL FEATURES BIEMMEDUE SUPER 200/21

Phase type: Three-phase
Power supply voltage: 400 V
Frequency: 50 Hz
Maximum pressure: 200 bar - 20 Mpa - 2900 psi
Maximum flow rate: 1260 Lt. /h
Pump: IP 47
Stop system: ACDS
Pump rotation: 1450 rpm
Maximum absorbed power: 8.4 KW
Maximum temperature: 140 ° C
Capacity; tank: 35 l
Capacity; detergent tank: 3 l
Length: 956 mm
Width: 610 mm
Height: 940 mm
Weight: 151 Kg.

Are you looking for a pressure washer with different characteristics? [HERE](#) you can find the entire BIEMMEDUE range or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Maximum output capacity (Lt/min): 1260
Tank capacity (L): 35
Transportability: Wheels and handles
Length (mm): 956
Width (mm): 610
Height (mm): 940
Dry weight (Kg): 151

maximum water temperature (°C): 140

Maximum input power (KW): 8.4

Pump rotation (rpm): 1450

Maximum pressure (bar-MPa-psi): 200 - 20 - 2900