


VITRIFRIGO MACS 7000 HEAT PUMP SINGLE- BLOCK NAUTICAL AIR CONDITIONER 7000 BTU/h



Product price:

1.391,32 € tax excluded

Product description:

VITRIFRIGO MACS7000 NAUTICAL AIR CONDITIONER

The VITRIFRIGO MACS7000 Nautical Air Conditioner represents the latest innovation in cooling systems, designed to ensure optimal comfort in single or adjacent environments.

With capacities ranging from 7,000 to 16,000 BTU/h, the VITRIFRIGO MACS7000 Nautical is suitable for a wide range of environments, offering the flexibility needed to meet various conditioning needs. Its monoblock structure, consisting of compressor, condenser, evaporator, and fan, makes it ideal for use in any season, ensuring constant comfort on board boats.

Thanks to its compact dimensions and lightweight of only 23 kg, the VITRIFRIGO MACS7000 Nautical is easy to install and suitable even for limited spaces. Its 230V/50Hz power supply ensures easy integration with the existing electrical system on board.

The technical specifications of the VITRIFRIGO MACS7000 Nautical are impressive: with a nominal cooling capacity of 7000 BTU/h and a nominal heating capacity of 7800 BTU/h, it can effectively manage indoor climate in any condition. Furthermore, its low energy consumption and operational efficiency make it an economical and environmentally friendly choice.

The treated air flow rate of 400 m³/h ensures uniform air distribution within the environment, while the recommended pump capacity of 600 l/h ensures optimal

operation of the conditioning system.

In summary, the VITRIFRIGO MACS7000 Nautical Air Conditioner represents the ideal solution for cooling on board, offering high performance, reliability, and unmatched comfort. With its advanced design and high-level technical features, it is the perfect choice for those seeking a superior quality cooling system for their vessel.

Technical Features VITRIFRIGO MACS7000 Nutical:

Net weight: 23 Kg

Power supply: 230V/50Hz

Width: 454 mm.

Height: 300 mm.

Depth: 273 mm.

Air delivery diameter: 102 mm.

Condensation drain pipe diameter: 18 mm.

Panelboard dimensions: 245 x 188 x 64 mm.

Nominal capacity in cooling mode (BTU/h): 7000

Rated capacity in heating mode (BTU/h): 7800

Rated consumption power (cooling mode) (kW): 0.6

Rated power consumption (heating mode) (kW): 0.7

Rated consumption in cooling mode (A): 2.6

Nominal consumption in heating mode (A): 3

Processed air flow rate (mc/h): 400

Recommended pump capacity (l/h): 600

VITRIFRIGO MACS7000 Nautical

Looking for a product with different technical characteristics? Here you can find the area dedicated to nautical air conditioners VITRIFRIGO or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase

Frequency (Hz): 50

Voltage (V): 230

Outlet diameter thread type (mm/inches): 102 - 4

Absorbed average current, refrigerating (A): 2.6

Absorbed average current, heater (A): 3

Inlet power, refrigerating (KW): 0.6

Inlet power, heater (KW): 0.7

Maximum air flow rate (m³/h): 400

Length (mm): 273

Width (mm): 454

Height (mm): 300

Product type: Air conditioner

Coolant: R410A

Weight (Kg): 23

Rated capacity in cooling mode (BTU/h): 7000

Nominal capacity in heating mode (BTU/h): 7800