



# CUMMINS AUTOMATIC TRANSFER SWITCH A066A016



**Product price:**

**1.310,00 € tax excluded**

## **Product description:**

CUMMINS AUTOMATIC TRANSFER SWITCH A066A016

GTEC transfer switches combine reliability and flexibility in a small, economical package for transferring loads between a utility and a generator set or between two generators.

Microprocessor control monitors the power supply to utilities and the standby generator. When mains power fails or is unsatisfactory, the control starts the generator, then transfers the load from the utility to the generator. When stable power returns, the switch automatically transfers the load to the grid.

If the main genset shuts down or is taken out of service, the switch starts the second genset and transfers the load.

The fully integrated controller is designed for practical functionality, with LED indicators and digital buttons for ease of use by the operator.

## TECHNICAL FEATURES.

Number of poles: 4  
Ampere range: 63 A  
Application Voltage: Multi-voltage 110/119 - 277/480 V  
Control Type: 12 Vdc  
Frequency: 50/60 Hz  
Protection class: IP 32  
Length: 680 mm  
Width: 570 mm  
Height: 231 mm  
Weight: 48 kg





---

Looking for an ATS switchboard with different technical characteristics? [HERE](#) you can find the area dedicated to automatic switchboards from CUMMINS or other specialized brands.

Images and technical data are not binding and may be subject to revision.

**Product features:**

Frequency (Hz): 50 / 60

Poles: 4

Protection degree: IP32

Current range (A): 63

Length (mm): 680

Width (mm): 570

Height (mm): 231

Product type: Switching Frame

Colour: Grey

Weight (Kg): 48

