



CUMMINS AUTOMATIC TRANSFER SWITCH A066A331



Product price:

1.560,00 € tax excluded

Product description:

CUMMINS AUTOMATIC TRANSFER SWITCH A066A331

GTEC transfer switches combine reliability and flexibility in a small, economical package for transferring loads between a utility and a generator set or between two generators.

Microprocessor control monitors the power supply to utilities and the standby generator. When mains power fails or is unsatisfactory, the control starts the generator, then transfers the load from the utility to the generator. When stable power returns, the switch automatically transfers the load to the grid.

If the main genset shuts down or is taken out of service, the switch starts the second genset and transfers the load.

The fully integrated controller is designed for practical functionality, with LED indicators and digital buttons for ease of use by the operator.

TECHNICAL FEATURES.

Number of poles: 4

Ampere range: 160 A

Application Voltage: Multi-voltage 110/119 to 277/480 V

Control Type: 12 Vdc

Frequenza: 50/60 Hz

Protection class: IP 32

Length: 950mm

Width: 650mm

Height: 231mm

Weight: 63 Kg



Looking for an ATS switchboard with different technical characteristics? [HERE](#) you can find the area dedicated to automatic switchboards from CUMMINS or other specialized brands.

Images and technical data are not binding and may be subject to revision.

Product features:

Frequency (Hz): 50 / 60

Poles: 4

Protection degree: IP32

Current range (A): 160

Length (mm): 950

Width (mm): 650

Height (mm): 231

Product type: Switching Frame

Colour: Grey

Weight (Kg): 63