



# PRAMAC LIFTER GS EVO 30 S2 TRANSPALLET MANUAL 1150x525 SINGLE ROLLER

**Product price:**

**681,00 € tax excluded**

## **Product description:**

PRAMAC LIFTER GS EVO 30 S2 TRANSPALLET MANUAL 1150x525 SINGLE ROLLER

The Pramac Lifter GS Evo 30 S2 is; a hand pallet truck designed to transport loads weighing up to 3000 kg. This pallet truck is equipped with a standard fork 1150 mm long and 525 mm wide, able to easily adapt to most transport needs.

The ergonomic design of the pallet truck, with a lever handle and a hydraulic pump lifting system, allows for easy maneuverability. and quick and safe lifting of loads. Furthermore, the integrated braking system ensures precise control of the pallet truck in any loading and unloading situation.

The Pramac Lifter GS Evo 30 S2 is; equipped with a high-strength steel frame, which guarantees greater durability and greater stability; during the transportation of loads. Furthermore, the pallet truck is; equipped with an accident prevention system, with a quick release mechanism of the forks in the event of a collision or impact.

This hand pallet truck is designed to be used in a variety of ways. easy to maintain and requires minimal maintenance due to its robust construction and quality; of the materials used. Additionally, the pallet truck's compact and lightweight design allows for easy transportation and storage, making it an ideal option for small to medium-sized warehouses and warehouses.

## TECHNICAL FEATURES PRAMAC LIFTER GS EVO 30 S2

Type of propulsion: Manual

Lifting: Manual

Guide system: Accompanying

Load capacity: 3000 kg

Front tyres: NYLON/POLY



Rear tyres: POLY  
Front track: 155 mm  
Rear track: 375 mm  
Lift height: 115 mm  
Drawbar height in driving position max: 1185 mm  
Drawbar height in driving position min: 710 mm  
Height of forks lowered: 85 mm  
Total length: 1550 mm  
Unit length: drive: 400 mm  
Total width: 525 mm  
Fork dimensions - Thickness: 50 mm  
Fork dimensions - Width: 150 mm  
Fork length: 1150 mm  
Fork width : 525 mm  
Free light in the middle; wheelbase: 35 mm  
Stow aisle for 800x1200 pallets: 2085 mm  
Turning radius: 1367 mm  
Service weight: 88 Kg

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to pallet trucks PRAMAC or other specialized brands

Non-binding images and technical data.

### Product features:

Drive: Manual  
Operator type: Pedestrian  
Load capacity (Kg): 3000  
Load centre distance (mm): 600  
Load axle to end forks (mm): 932  
Wheel base (mm): 1192  
Service weight (Kg): 88  
Axle load, laden rear (Kg): 2196  
Axle load, laden front (Kg): 892  
Axle load, unladen front (Kg): 59  
Axle load, unladen rear (Kg): 29  
Tyres: front wheels: POLY.I. / NYLON  
Tyres: rear wheels: NYLON  
Diameter steering wheels (mm): 200  
Width steering wheels (mm): 55  
Diameter load rollers (mm): 82  
Width load rollers (mm): 60

---

Quantity rear wheels: 4  
Rear balancing axle: No  
Tread front (mm): 155  
Tread rear (mm): 375  
Lift height (mm): 115  
Height of tiller in drive position max (mm): 1185  
Height lowered (mm): 85  
Overall length (mm): 1550  
Length to face of forks (mm): 400  
Overall width (mm): 525  
Thickness fork (mm): 50  
Width fork (mm): 150  
Length fork (mm): 1150  
Distance between fork arms (mm): 525  
Ground clearance at centre of wheelbase (mm): 35  
Aisle width (mm): 2048  
Turning radius (mm): 1367  
Lifting speed laden (strokes): 13  
Lifting speed unladen (strokes): 13  
Weigher: No