



# VICTRON MultiPlus-II 12/3000/120-32 Charger- Inverter 12V 32A

**Product price:**

**1.170,00 € tax excluded**

## Product description:

VICTRON MultiPlus-II 12/3000/120-32 Charger-Inverter 12V 32A

VICTRON MultiPlus-II 12/3000/120-32 powerful pure sine wave inverter and charger adaptive charging technology and a high-speed AC transfer switch.

The VICTRON MultiPlus-II 12/3000/120-32 Charger-Inverter is a versatile energy management solution that amplifies the features of the MultiPlus by offering the additional option of an Energy Storage System (ESS). The VICTRON MultiPlus-II 12/3000/120-32 operates as an inverter/charger with an extended PowerControl and PowerAssist capacity of up to 32 A respectively, thanks to an external sensor option.

Designed for professional off-grid applications such as marine navigation, yachts, vehicles and agriculture, the VICTRON MultiPlus-II 12/3000/120-32 has a built-in anti-isolation feature and an ever-changing list of certifications from various countries for ESS applications. System configurations are flexible and suitable for various needs, as described in the ESS Design and Configuration Manual.

The PowerControl and PowerAssist functions enhance the capacity of the grid or generator. By setting a maximum input current from the grid or generator, the VICTRON MultiPlus-II 12/3000/120-32 intelligently manages loads and prioritizes battery charging, preventing overcharging.

Solar energy integration enables the VICTRON 12/3000/120-32 Battery Charger-Inverter to operate autonomously by connecting to photovoltaic systems and other alternative sources. It is compatible with both solar charge controllers and grid-connected inverters.

TECHNICAL FEATURES VICTRON MultiPlus-II 12/3000/120-32

PowerControl and PowerAssist: Yes



Transfer switch: 32 A  
Maximum AC input current: 32 A

#### INVERTER

DC input voltage range: 9.5 to 17 V  
Output voltage: 230 VAC  $\pm$  2 %  
Frequency: 50 Hz  $\pm$  0.1 % (1)  
Continuous output power at 25?: 3000 VA  
Continuous output power at 25? / 40? / 65?: 2400 W / 2200 W / 1700 W  
Maximum apparent input current: 3000 VA  
Peak power: 5500 W  
Maximum efficiency: 93 %  
Zero load power supply: 13 W  
No-load power in AES mode: 9 W

#### CHARGER

AC input Voltage range: 187-265 VAC  
Input frequency: 45-65Hz  
'Absorption' charging voltage: 14.4 V  
'Trickle' charging voltage: 13.8 V  
Accumulation mode: 13.2 V  
Maximum battery charging current: 120 A  
Battery temperature sensor: Yes

Protection category: IP22  
Width: 141 mm  
Length: 275 mm  
Height: 546 mm  
Weight: 19 kg

Looking for a product with different technical specifications? Here you can find the complete range of VICTRON chargers and inverters, as well as other specialized brands.

Non-binding images and technical data.

#### Product features:

Phase: Single phase  
Frequency (Hz): 50  
Voltage (V): 187-265  
Protection degree: IP21  
Output voltage (V): 230  
Nominal current (A): 14.4

Charging voltage (V): 12

Length (mm): 141

Width (mm):

Height (mm): 546

Overload protectors: Yes

Input voltage (V): 12

Kind of wave: Pure Sinusoidal

Continuous power (W): 2400

Colour: Blue

Weight (Kg): 19