



PRAMAC P15000 GENERATOR 14KVA SINGLE PHASE / THREE PHASE STAGEV

Product price:

8.431,50 € tax excluded

Product description:

PRAMAC P15000 GENERATOR 14KVA SINGLE PHASE / THREE PHASE STAGEV

The PRAMAC P15000 single/three-phase generator is equipped with a StageV Honda GX690 gasoline engine capable of delivering a power output of 14KVA, complete with Compound voltage regulator (optional AVR).

The PRAMAC P15000 can be chosen with or without AVR.

The PRAMAC P15000 generator is a powerful device designed to provide a reliable source of energy, whether in single-phase or three-phase mode, with a capacity of 14KVA. This generator is known for its easy installation and operation, making starting and stopping a breeze thanks to clear and intuitive controls. Additionally, it features an automatic shutdown function in case of low oil level, ensuring engine protection.

One of the distinctive strengths of this generator is the high-quality components, ensuring reliable and long-lasting performance. Despite its power, the generator is surprisingly lightweight and compact, making it extremely practical to use and transport in any situation. The modern design adds an aesthetic touch to its efficiency.

With a 40-liter tank, the PRAMAC P15000 generator has an incredible consumption rate of only 6 liters per hour, guaranteeing approximately 6 hours of continuous work. This efficiency in fuel consumption makes it an economical and sustainable choice for providing power in emergency situations or in locations without a stable electrical supply.

The generator is equipped with electric start, further simplifying its usage. It is also equipped with a digital control unit and an advanced protection system to ensure safe operation and generator protection. These features make it ideal for a wide range of applications, including use on

construction sites, outdoor events, and emergency situations.

CONTROL SECTION

- CONTROL UNIT with 3-position key: OFF, ON local start, REM remote start.
- 2-wire remote start/stop (REM)
- Connector for RSS panel (available as an accessory).
- Alarm buzzer

CONTROL PANEL

- Display: LCD with icons (52x35mm)
- Group parameters: V- Hz - RPM - A (single-phase) - kVA - kWe - Fuel level (%)
- Parameter control and/or firmware transfer via smart NFC connection

STAGEV EMISSIONS REGULATION

The PRAMAC P15000 is equipped with Stage V "mobile" engine technology, as required by European Regulation 2016/1628. These new engine technologies exponentially reduce particulate and nitrogen oxide emissions released into the environment from the generator, ensuring a 200% reduction in environmental impact compared to standard engine technologies.

TECHNICAL SPECIFICATIONS PRAMAC P15000

Phase Type: Single/Three-Phase

Continuous Power: 14 KVA / 11.2 KW

Maximum Power: 15.7 KVA / 12.6 KW

VAC Voltage: 230/400 V

Frequency (Hz): 50

Voltage Regulator: Compound (Optional AVR)

Starting: Electric

Engine: Honda GX690

RPM (Revolutions per Minute): 3000

Emissions Regulation: StageV

Fuel: Gasoline

Outlet Panel: 1 x SCHUKO 230V 16A - 1 x CEE 230V 16A 2P - 1 x CEE 400V 16A 3P - 1 x CEE 400V 32A 3P

Tank Capacity: 40 l

Consumption @ 75% Load: 5.96 l/h

Autonomy @ 75% Load: 6.71 h

Sound Pressure: 64 dB(A) @ 7m

Length: 1205 mm

Width: 754 mm

Height: 1035 mm

Net Weight: 325 Kg

Looking for a generator with different technical specifications? You can find a dedicated area for PRAMAC and other specialized brand generators [HERE](#).

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 12.6

Continuous power three phase (KW): 11.2

Maximum power three phase (KVA): 15.7

Continuous power three phase (KVA): 14

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x SCHUKO 230V 16A - 1 x CEE 230V 16A 2P - 1 x CEE 400V 16A 3P - 1 x CEE 400V 32A 3P

Engine: Honda GX690

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 688

Oil capacity (L): 1.9

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 40

Consumption (L/h): 5.96 at 75% load

Running time (h): 6.71 at 75% load

Acoustic power: 92 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1205

Width (mm): 754

Height (mm): 1035

Dry weight (Kg): 325

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Honda