

GENERATING SET 45KVA WITH AUTOMATIC CONTROL PANEL



Product price:

11.663,00 € tax excluded

Product description:

Single/three-phase 45KVA generator super-silenced with automatic control pane

Technical characteristics of the generator:

Phase type: Single-phase / Three-phase
Maximum three-phase power: 40 KW / 50 KVA
Three-phase continuous power: 36 KW / 45 KVA
Maximum single-phase power: 13.33 KW / 16.67 KVA
Single-phase continuous use power: 12 KW / 15 KVA
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Motor: FPT NEF N45AM1A
Engine speed: 1500 rpm
Starting: Electric
Consumption: 8.8 Lt/h at 75% load
Length: 2000 mm
Width: 850 mm
Height: 1275 mm
Weight: 930 Kg
Super-silenced
AVR

Images and technical data are not binding.

Product features:



Phase: Single phase / Three phase
Maximum power single phase (KW): 13.3
Continuous power single phase (KW): 12
Maximum power single phase (KVA): 16
Continuous power single phase (KVA): 15
Maximum power three phase (KW): 40
Continuous power three phase (KW): 36
Maximum power three phase (KVA): 50
Continuous power three phase (KVA): 45
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: FPT NEF N45AM1A
Emissions Regulations: Stage 2
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 4500
Number cylinders: 4
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 104 x 132
Fuel tank capacity (L): 100
Consumption (L/h): 8.8
Running time (h): 11.4
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 2000
Width (mm): 850
Height (mm): 1275
Dry weight (Kg): 930
AVR: Yes
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: FPT Iveco