



CUMMINS C400D5Q GENERATOR 400KVA SINGLE/THREE PHASE SILENCED



Product price:

52.169,00 € tax excluded

Product description:

CUMMINS C400D5Q GENERATOR 400KVA SINGLE/THREE PHASE SILENCED

The CUMMINS C400D5Q generator is equipped with a Cummins QSG12-G3 diesel-powered engine and is capable of delivering a maximum output of 400KVA, complete with AVR voltage regulator.

The CUMMINS C400D5Q is equipped with the **PowerCommand 2.2 unit**, which enables the display of all electrical parameters of the engine and generator, the functions, statuses of the genset, the complete management of the genset, and the display of system errors or alarms should they occur. The unit provides a simple interface, automatic/manual and remote start/stop control and shutdown fault indication. The integration of all functions in a single control provides greater reliability and performance than conventional genset control systems.

Standard features of the Cummins C400D5Q generator include the Cummins diesel engine, a robust industrial 4-stroke that ensures reliable power generation and fast responsiveness to load changes. The alternator, part of the Stamford S series, is self-exciting, ensuring efficient generation. An optional permanent magnet alternator is also available.

Control is via the microprocessor-based PowerCommand monitoring, which ensures accurate genset control. Open and encapsulated versions of the genset are available.

The Cummins C400D5Q generator is backed by a comprehensive warranty and an extensive network of distributors and dealers. In addition, the engine is equipped with a 230 V coolant heater as standard, which ensures starting even in low ambient temperatures by circulating the heated coolant inside.

In addition, it is equipped with an automatic start via the ATS panel, which allows autonomous



start-up in the event of a power failure.

Thanks to the advanced unit, the generator is equipped with :

PC-based software service tool

Inpower Modbus interface for interconnection with PLC/BMS

Configurable inputs and outputs

Configurable alarm inputs to trigger a shutdown or warning response

ATS AUTOMATIC TRANSFER SWITCH ARRANGEMENT

The CUMMINS C400D5Q generator is prepared for connection to the Automatic Transfer Switch ATS. Thanks to which you no longer have to worry about blackouts, since in the event of a power failure this panel is able to switch on the unit and allow you to continue your activity without losing your work data.

CUMMINS C400D5Q TECHNICAL CHARACTERISTICS

Phase type: Single-phase / Three-phase

Continuous power: 360 KVA / 288 KW

Maximum Power: 400 KVA / 320 KW

Engine: Cummins QSG12-G3

Powersupply: Diesel

Engine speed: 1500 rpm

Speed control: Mechanical

Alternator: Stamford S4L1D-F41

Emission standard: Not Emitted

Starter: Electric / Automatic

Voltage regulator: AVR

Voltage: 230/400 V

Frequency: 50 Hz

Socket panel: Terminal box

Tank capacity: 995 l

Consumption at 75 % load: 55.27 l/h

Autonomy at 75 % load: 18 h

Length: 4015 mm

Width: 1400 mm

Height: 2495 mm

Dry weight: 3795 kg

Looking for a generator with different technical characteristics? [HERE](#) you can find the full range of CUMMINS generators and other specialised brands.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 320
Continuous power three phase (KW): 288
Maximum power three phase (KVA): 400
Continuous power three phase (KVA): 360
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: 4 stroke
Emissions Regulations: Not Emitted
Engine rpm (rpm): 1500
Speed governor: Mechanical
Number cylinders: 6
Cylinders' position: In line
Cooling: Coolant Liquid
Poles: 4
Bore x stroke (mm): 132 x 144
Fuel tank capacity (L): 995
Consumption (L/h): 55.27 to 75% of the load
Running time (h): 18 to 75% of the load
Acoustic pressure: 71 dB(A) at 7 m
Length (mm): 4015
Width (mm): 1400
Height (mm): 2495
Dry weight (Kg): 3795
Silenced: Yes
Brushes: No
Product type: Generator
Control unit: PowerCommand 2.2
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Cummins
Precision of voltage regulation: $\pm 1\%$