



VISA P105GX GENERATOR SET SILENCED 100 KVA AVR

Product price:

18.408,00 € tax excluded

Product description:

GENERATING UNIT VISA P105GX

The VISA P105GX silenced land-based generator set, rated at 100 KVA in continuous use and AVR, mounts top brand components: the VISA P105GX model uses a reliable PERKINS 1104C-44TAG2 4-cylinder, 1500-rpm diesel engine and a **STAMFORD UCI274C** alternator equipped with AVR with 1% voltage regulation accuracy.

The VISA industrial power generators feature silenced casings and tropicalized treatment, thus they are suitable for use in hot climates; in particular the VISA P105GX is water-cooled, which guarantees excellent heat management.

The robust frame of the silenced VISA P105GX genset contains a capacious 160-litre tank, guaranteeing a 9-hour autonomy at 75% load; furthermore, the dimensions of this generator are optimised for its transport by truck and its storage in a 40' HC container.

Technical characteristics of the VISA P105GX generator set:

Phase type: Three-phase

Maximum three-phase power: 110 KVA

Three-phase continuous power: 88 KW

Maximum three-phase power: 100 KVA

Three-phase continuous power: 80 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: PERKINS 1104C-44TAG2

Engine speed: 1500 rpm

Starter: Electric

Consumption: 17.1 Lt/h at 75% load

Length: 2560 mm



Width: 1040 mm
Height: 1805 mm
Weight: 1650 Kg
Supersilenced
AVR

If you are looking for a product such as the VISA P105GX then you can browse the entire VISA generator range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Three phase
Maximum power three phase (KW): 88
Continuous power three phase (KW): 80
Maximum power three phase (KVA): 110
Continuous power three phase (KVA): 100
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Sockets configuration: Morsettiera
Engine: Yanmar L70N
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Starting system: Elettrico
Engine capacity (cm³): 686
Number cylinders: 4
Cooling: Water
Poles: 4
Fuel tank capacity (L): 160
Consumption (L/h):
Running time (h): 9.3
Length (mm):
Width (mm): 1040
Height (mm): 1805
Dry weight (Kg): 1650
Silenced: Yes
Product type: Generator
Voltage regulator: AVR
Engine manufacturer: Perkins