

# GENSET 80KVA WITH MANUAL PANEL



Product price:

**14.464,00 € tax excluded**

## Product description:

Single/three-phase 80KVA generator super-silenced with manual control panel

Genset is a single/three phase 80KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and lined with sound-absorbing material with high noise reduction, making the super-silenced.

generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. Generator is equipped with an electric starter with a low fuel consumption battery, consuming only 15 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

Generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## Technical characteristics of the Genset:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 70.4 KW / 88 KVA

Three-phase continuous power: 64 KW / 80 KVA

Maximum single-phase power: 23.47 KW / 29.33 KVA

Single-phase continuous use power: 21.33 KW / 26.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT NEF N45SM3

Engine speed: 1500 rpm

Starting: Electric

Consumption: 15 Lt/h at 75% load

Length: 2300 mm

Width: 1050 mm  
Height: 1590 mm  
Weight: 1345 Kg  
Super-silenced  
AVR

If you are looking for a similar product then you can browse the entire range of generators or other types of products in our catalogue to find the one that best suits your needs.

Non-binding images and technical data.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 23.47  
Continuous power single phase (KW): 21.33  
Maximum power single phase (KVA): 29.3  
Continuous power single phase (KVA): 26.67  
Maximum power three phase (KW): 70.4  
Continuous power three phase (KW): 64  
Maximum power three phase (KVA): 88  
Continuous power three phase (KVA): 80  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: FPT (IVECO) NEFN45SM3  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 4500  
Number cylinders: 4  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 104 x 132  
Fuel tank capacity (L): 120  
Consumption (L/h): 15  
Running time (h): 8  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 2300

Width (mm): 1050

Height (mm): 1590

Dry weight (Kg): 1345

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: FPT Iveco