



HYUNDAI FULLPOWER HP7500CXE-3 COD. 65223 STAGEV

Product price:

1.333,52 € tax excluded

Product description:

HYUNDAI FULLPOWER HP7500CXE-3 DIESEL GENERATOR SINGLE-PHASE/THREE-PHASE STAGEV AVR 5 KW

HYUNDAI FULLPOWER HP7500CXE-3 single/three phase generator, is equipped with a 4-stroke **StageV** engine supplied by diesel, delivers a maximum power of 5 KW, complete with AVR voltage regulator.

HYUNDAI FULLPOWER HP7500CXE-3 is equipped with electric start with battery.

The HYUNDAI FULLPOWER HP7500CXE-3 generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI FULLPOWER HP7500CXE-3 generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI FULLPOWER HP7500CXE-3 has a completely steel structure and a tank with a maximum capacity of 12,5 lt.

EMISSION STANDARD STAGEV

HYUNDAI FULLPOWER HP7500CXE-3 is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and ensure a 200% reduction in environmental impact compared to standard engines.

TECHNICAL CHARACTERISTICS HYUNDAI FULLPOWER HP7500CXE-3:

Maximum three-phase power: 5 KW



Three-phase continuous power: 4.5 KW
Maximum power Single-phase: 5 KW
Single-phase continuous power: 4.5 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: 4-stroke
Starter: Electric
Length: 740 mm
Width: 520 mm
Height: 570 mm
Weight: 100 Kg
AVR

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5
Continuous power single phase (KW): 4.5
Maximum power single phase (KVA): 6.25
Continuous power single phase (KVA): 5.6
Maximum power three phase (KW): 5
Continuous power three phase (KW): 4.5
Maximum power three phase (KVA): 6.25
Continuous power three phase (KVA): 5.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V - 1 x 230V
Engine: 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 456
Oil capacity (L): 1.1
Alternator: Copper windings
Length (mm): 740
Width (mm): 520

Height (mm): 570
Dry weight (Kg): 100
Product type: Generator
Voltage regulator: AVR