

PRAMAC GDW150PFNE Genset Silenced 148KVA

Product price:

31.515,00 € tax excluded

Product description:

NO

PRAMAC GDW150PFNE Silenced Genset 148KVA

PRAMAC GDW150PFNE is the ideal silent genset to give you maximum power and reliability in any situation.

With its ESP of 148 kVA and PRP of 135 kVA, it is perfect for powering a wide range of consumers,

both domestic and professional.

PRAMAC GDW150PFNE Reliability guaranteed:

Perkins 1106A-70TG1 engine, certified Non Emission Stage 5, for safe and environmentally friendly operation.

Mecc Alte ECP34 2M 4C alternator, with copper winding and electronic voltage regulator, for stable and precise current delivery.

Exceptionally quiet operation:

Enclosure made of modular galvanised steel panels, suitably treated to resist corrosion and aggressive environmental conditions.

High-quality sound-absorbing materials and a residential muffler guarantee excellent soundproofing performance and a low level of noise emission.

Easy to operate and maintain:

Large side doors for easy access for service and maintenance.

Doors equipped with lockable handles.

Base frame with welded steel profiles.

Appropriately dimensioned anti-vibration mounts.

Removable support feet.

Lifting eyebolts.

Protection of rotating parts against accidental contact.

Accessible earthing point.

R

Technical characteristics PRAMAC GDW150PFNE silenced genset:

Length (L): 3090 mm Width (W): 1100 mm Height (H): 1852 mm Weight: 1827 Kg Noise emission level Acoustic (LWA): 97 dB(A) Sound pressure @ 1 m: 79 dB(A) Acoustic pressure @ 7 m: 68 dB(A) Battery voltage: 12 V Voltage: 400/230 V Frequency: 50 Hz Phases: 3 Performance: ESP power: 148 kVA PRP power: 135 kVA Engine: Model: Perkins 1106A-70TG1 Displacement: 7010 cm³ Fuel: Diesel Alternator: Model: Mecc Alte ECP34 2M 4C Winding: Copper Voltage regulator: Electronic

Ø.

PRAMAC GDW150PFNE: the ideal choice for anyone looking for a powerful, reliable and quiet genset.

Are you looking for a genset with different technical characteristics? HERE you can find the area dedicated to PRAMAC generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase Maximum power three phase (KW): 118.4 Continuous power three phase (KW): 108 Maximum power three phase (KVA): 148 Continuous power three phase (KVA): 135 Fuel: Diesel Frequency (Hz): 50

R

Voltage (V): 230 / 400 Engine: Perkins 1106A-70TG1 Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Electric Engine capacity (cm³): 7010 Number cylinders: 6 Cylinders' position: In line Cooling: Water Alternator: Mecc Alte ECP34 2M 4C Poles: 4 Acoustic pressure: 68 dB(A) at 7 m Length (mm): 3090 Width (mm): 1100 Height (mm): 1852 Dry weight (Kg): 1827 Silenced: Yes Super silenced: Yes ATS Switch device : Optional Engine manufacturer: Perkins

R

