



CUMMINS C170D5Q GENERATOR 170KVA SINGLE/THREE PHASE SILENCED

Product price:

20.296,00 € tax excluded

Product description:

CUMMINS C170D5Q GENERATOR 170KVA SINGLE/THREE PHASE SILENCED

The CUMMINS C170D5Q generator is equipped with a Cummins 6BTAA5.9-G7 diesel-powered engine and is capable of delivering a maximum output of 170KVA, complete with AVR voltage regulator.

Generator set control PowerStart 600 – The PowerStart control is a microprocessor-based generator set monitoring and control system. The control provides a simple operator interface to the generator set, auto/ manual and remote start/stop control and shutdown fault indication. The integration of all control functions into a single control provides enhanced reliability and performance compared to conventional generator set control systems. This control has been designed and tested to meet the harsh environment in which gensets are typically applied.

Standard features of the Cummins C170D5Q generator include the Cummins diesel engine, a robust industrial 4-stroke that ensures reliable power generation and fast responsiveness to load changes. The alternator, part of the Stamford series, is self-exciting, ensuring efficient generation. An optional permanent magnet alternator is also available.

The Cummins C170D5Q generator is backed by a comprehensive warranty and an extensive network of distributors and dealers. In addition, the engine is equipped with a 230 V coolant heater as standard, which ensures starting even in low ambient temperatures by circulating the heated coolant inside.

In addition, it is equipped with an automatic start via the ATS panel, which allows autonomous start-up in the event of a power failure.

ATS AUTOMATIC TRANSFER SWITCH ARRANGEMENT





The CUMMINS C170D5Q generator is prepared for connection to the Automatic Transfer Switch ATS. Thanks to which you no longer have to worry about blackouts, since in the event of a power failure this panel is able to switch on the unit and allow you to continue your activity without losing your work data.

CUMMINS C170D5Q TECHNICAL CHARACTERISTICS

Phase type: Single-phase / Three-phase Continuous power: 155 KVA / 124 KW Maximum Power: 170 KVA / 136 KW Engine: Cummins 6BTAA5.9-G7

Power supply: Diesel Engine speed: 1500 rpm Alternator: Stamford UC274F Emission standard: Not Emitted Starter: Electric / Automatic Voltage regulator: AVR Voltage: 230/400 V

Frequency: 50 Hz

Socket panel: Terminal box

Tank capacity: 400 l

Consumption at 75 % load: 31,5 l/h

Autonomy at 75 % load: 13 h

Length: 3100 mm Width: 1180 mm Height: 1950 mm Dry weight: 2039 Kg

Looking for a generator with different technical characteristics? HERE you can find the full range of CUMMINS generators and other specialised brands.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase Maximum power three phase (KW): 136 Continuous power three phase (KW): 124 Maximum power three phase (KVA): 170 Continuous power three phase (KVA): 155

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400





Sockets configuration: Morsettiera

Engine: 4 Tempi

Emissions Regulations: NON EMISSIONATO

Engine rpm (rpm): 1500 Number cylinders: 6 Cylinders' position: In line

Cooling: Liquid

Poles: 4

Fuel tank capacity (L): 400 Consumption (L/h): 31.5

Running time (h): 13 at 75% of the load Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3100 Width (mm): 1180 Height (mm): 1950 Dry weight (Kg): 2039

Silenced: Yes Brushes: No

Product type: Generator ATS Switch device: Optional

Voltage regulator: AVR

Engine manufacturer: Cummins
Precision of voltage regulation: ± 1%