

BM2 SUSETTE 20015 High Pressure Washer 200 bar



Product price:

2.966,17 € tax excluded

Product description:

BM2 SUSETTE 20015 HIGH PRESSURE WASHER 200 BAR

The BM2 SUSETTE 20015 High Pressure Washer 200 bar offers an excellent solution for high-pressure cleaning in the professional sector. Equipped with advanced technologies and innovative features, this pressure washer is designed to ensure superior performance and optimal reliability in a wide range of applications.

The ACDS system of the BM2 SUSETTE 20015 200 bar provides advanced control with delayed shutdown and the option for connection to a diagnostic reader for precise performance monitoring. The pumps with ceramic pistons and brass head ensure exceptional durability and constant pressure during use, while the 1450 rpm motor provides reliable power.

The protection of the motor/pump coupling with special lubricant containment systems guarantees greater durability and reliability of the system, particularly in the BM2 SUSETTE 20015 model. Next-generation pumps, high-performance and low-maintenance, along with the pressure and steam production regulation valve, allow effective delivery of high-pressure detergent.

The BM2 SUSETTE 20015 is equipped with a range of features designed to maximize convenience and ease of use. These include a feeder water tank with float valve, an externally inspectable water filter, and a boiler pre-ventilation system for quick startup.

Designed with particular attention to safety and durability, the BM2 SUSETTE 20015 includes motor thermal protection, automatic shutdown after 20 minutes of non-use, and integrated leakage control. It is also prepared for optional installation of a limescale kit to protect the system from deposits.

The BM2 SUSETTE 20015 200 bar offers easy portability and maneuverability, with two free wheels and two swivel wheels with brakes for greater stability and control during use. With high-level technical specifications, including a maximum pressure of 200 bar, a maximum flow rate of 900 Lt./h, and a maximum temperature of 140 °C, it is capable of tackling the most challenging tasks with ease and efficiency.

Technical Features BM2 SUSETTE 20015:

Phase type: Three-phase

Fuel: Diesel

Frequency: 50 Hz

Voltage: 400 V

Maximum pressure: 200 bar - 20 MPa - 2900 psi

Maximum flow rate: 900 Lt./h

Pump: IP E2

Shut-off system: ACDS

Pump rotation: 1450 rpm

Max. power consumption: 6.7 KW

Power supply: 400V - 3ph - 50Hz

Mas temperature: 140 °C

Diesel tank: 35 lt

Detergent tank: 3 lt

Length: 956 mm

Width: 610 mm

Height: 940 mm

Weight: 128 Kg.

BM2 SUSETTE 20015

Are you looking for a hydrocleaner with different features? Here you can find the full range BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Pump type: IP E2

Maximum output capacity (Lt/min): 900
Transportability: Wheels and handles
Fuel tank capacity (L): 35
Length (mm): 956
Width (mm): 610
Height (mm): 940
Dry weight (Kg): 128
Feed Type: 400V - 3ph - 50Hz
maximum water temperature (°C): 140
Maximum input power (KW): 6.7
Pump rotation (rpm): 1450
Maximum pressure (bar-MPa-psi): 200 - 20 - 2900
Stop system: ACDS
Detergent tank: 3