



PRAMAC GBW10Y ENCLOSURE WITH MANUAL CONTROL PANEL



Product price:

8.845,00 € tax excluded

Product description:

PRAMAC GBW10Y MCP Three-Phase 7.4 KW Super Silent Generator

The PRAMAC GBW10Y three-phase generator with 7.4 KW power, powered by a diesel engine running at 1500 RPM and equipped with electric start. The alternator of the PRAMAC GBW10Y generator has brushes with a compound voltage regulator. The Yanmar diesel engine makes the GBW10Y generator highly reliable as it is built and designed using top-quality materials.

Thanks to its casing, this generator is super silent. The PRAMAC GBW10Y three-phase generator is suitable for outdoor use in construction sites or for small professional outdoor jobs. Easy to transport and maneuver thanks to its wheeled base.

Technical Specifications of the PRAMAC GBW10Y MCP Three-Phase Generator:

Maximum Three-Phase Power: 7.47 KW

Continuous Three-Phase Power: 6.81 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV76-GPGE

Start: Electric

Consumption: 2.6 Lt/h at 100% load

Dimensions: Length: 1645 mm, Width: 870 mm, Height: 1072 mm

Weight: 460 Kg

Compound Voltage Regulator



**Outlets:**

1 3P+N+T CEE 400V 32A

1 3P+N+T CEE 400V 16A

2 2P+T CEE 230V 16A

1 230V 16A SCHUKO

The PRAMAC GBW10Y power generator is a professional diesel generator developed by Pramac with the features and equipment necessary to achieve a superior class product. The PRAMAC GBW10Y generator, with its low noise level, is the ideal generator for use in residential areas or outside working hours. The GBW10Y generator is equipped with a reliable diesel engine, top-quality components, and complete instrumentation. Its casing is tiltable for easy access to the maintenance area.

If you are looking for a generator like the GBW10Y MCP three-phase power generator, we recommend browsing our catalog of ground generators to find the one that best suits your needs.

Images and technical data are indicative only.

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.47

Continuous power three phase (KW): 6.81

Maximum power three phase (KVA): 9.34

Continuous power three phase (KVA): 8.51

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV76-GPGE, naturally aspirated

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line



Oil capacity (L): 3.5

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 25.6 at 75% of the load / 19.2 at 100% of the load

Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 460

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar