

PRAMAC GBW15P HOOD WITH AUTOMATIC CONTROL PANEL



Product description:

PRAMAC GBW15P ACP Three-phase 11.2 KW Super Silent Generator

The PRAMAC GBW15P three-phase generator with 11.2 KW power has a diesel engine running at 1500 rpm. The PRAMAC GBW15P generator is equipped with an electric start. The alternator of the PRAMAC GBW15P generator has brushes with a compound voltage regulator. The Perkins diesel engine makes the GBW15P generator highly reliable as it is built and designed using top-quality materials.

Thanks to its casing, this generator is super silent. Additionally, it is easy to transport, install, and position thanks to its compact size, making this model ideal for emergency power, construction, mobile workshops, and industrial applications. The PRAMAC GBW15P three-phase generator is suitable for outdoor use on construction sites or for small professional outdoor jobs.

Technical specifications of the PRAMAC GBW15P Three-phase generator:

- Maximum Three-phase Power: 11.28 KW
- Continuous Three-phase Power: 10.18 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Perkins 403D-15G
- Start: Electric
- Consumption: 3.6 Lt/h at 100% load
- Length: 1645 mm
- Width: 870 mm
- Height: 1072 mm
- Weight: 550 Kg
- Compound

Automatic Control Panel ACP:

Integrated panel connected to the generator, with a microprocessor control module that gathers all the electronic control, monitoring, and signaling circuits. Direct command terminal block for switching (ACP)

- N.1 3P+N+T CEE 400V 32A

The PRAMAC GBW15P power generator is a professional diesel generator developed by Pramac with the characteristics and equipment necessary to obtain a superior class product. The PRAMAC GBW15P power generator, with its low noise level, is the ideal generator for use in residential areas or during non-working hours.

The GBW15P generator is equipped with a reliable Perkins diesel engine, top-quality components, and complete instrumentation.

If you are looking for a generator like the GBW15P three-phase power generator, we recommend browsing our catalog of terrestrial generators to find the one that best suits your needs.

Images and technical data are non-binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Emissions Regulations: Stationary Use

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1496

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6

Cooling: Water

Alternator: Linz E1S13MD, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load

Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 550

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Compound

Engine manufacturer: Perkins