



BM2 MIDIA 16015 TSD High Pressure Cleaner 160 bar

Product price:

1.337,77 € tax excluded

Product description:

BM2 MIDIA 16015 TSD HIGH PRESSURE CLEANER 160 BAR

The BM2 MIDIA 16015 TSD is a high-quality cold water pressure washer designed to meet the most demanding cleaning needs.

With its pressure of 160 bar and flow rate of 900 lt/h, this machine is able to remove even the most stubborn dirt from

surfaces such as floors, vehicles, machinery and more.

Brass Pump Head and Piston Rod Models: The BM2 MIDIA 16015 TSD is equipped with brass pump heads,

which guarantee greater resistance to wear and a longer service life. This piston rod model offers high performance and

reliable operation.

Delayed and Immediate Shut-Off: The BM2 MIDIA 16015 TSD features a delayed shut-off that helps to prolong the life of the pump.

High-Efficiency Motor and 1450 rpm Rotation: The BM2 MIDIA 16015 TSD is powered by a high-efficiency motor that

guarantees optimal performance and low energy consumption. The motor's 1450 rpm rotation ensures quiet and

smooth operation.

Low-Pressure Detergent Delivery: This pressure washer features a low-pressure detergent delivery system that allows

you to apply detergent directly to the surface to be cleaned with precise control.

Adjustable Spray Angle and Motor Thermal Protection: The spray angle is adjustable to adapt to different cleaning needs.





Motor thermal protection protects the machine from overloads.

AISI 430 Cover, Anti-Track Wheels and Inspectable Water Filter: The BM2 MIDIA 16015 TSD is equipped with

an AISI 430 stainless steel cover that guarantees greater resistance to corrosion. The anti-track wheels facilitate the

transport of the machine, while the inspectable water filter helps to protect the pump from debris.

Lance Holder and Hose Reel Pre-Wiring: This pressure washer comes with a standard lance holder for added convenience.

It is also pre-wired for the installation of an optional hose reel.

Technical Specifications BM2 MIDIA 16015 TSD:

Phase type: Three-phase

Frequency: 50 Hz Voltage: 400 V

Maximum pressure: 160 bar - 16 Mpa - 2300 psi

Maximum flow rate: 900 Lt./h

Pump: IP E1

Stop system: TSD

Pump speed: 1450 rpm

Maximum absorbed power: 4.5 KW Supply voltage: 400 V - 3ph - 50Hz

Cleaning agent tank: 5 lt Maximum inlet temp: 40 °C Pallet quantities: 16 pcs

Length: 810 mm. Width: 380 mm. Height: 870 mm. Weight: 50 Kg.

BM₂

Are you looking for a hydrocleaner with different features? Here you can find the full range BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:





Phase: Three phase Frequency (Hz): 50 Voltage (V): 400 Pump type: IP E1

Maximum output capacity (Lt/min): 900 Transportability: Wheels and handles

Length (mm): 810 Width (mm): 380 Height (mm): 870

Feed Type: 400V - 3ph - 50Hz

maximum water temperature (°C): 40

Weight (Kg): 50

Maximum input power (KW): 4.5

Pump rotation (rpm): 1450

Maximum pressure (bar-MPa-psi): 160 - 16 - 2300

Stop system: TSD Detergent tank: 5

