

# PRAMAC GBW15Y APERTO CON QUADRO COMANDO AUTOMATICO



## Product description:

Motore Diesel. Raffreddamento ad acqua. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica. Quadro manuale MCP fornito di serie con 5 prese

L'immagine è puramente indicativa

## Product features:

Phase: Three phase

Maximum power three phase (KW): 11.44

Continuous power three phase (KW): 10.4

Maximum power three phase (KVA): 14.3

Continuous power three phase (KVA): 13

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Engine: Yanmar 3TNV88-BGPGE, naturally aspirated

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1642

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6.9

Cooling: Water

Alternator: Linz E1S13MD, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.8 at 75% of the load / 3.8 at 100% of the load

Running time (h): 18 at 75% of the load / 13.5 at 100% of the load

Length (mm): 1600

Width (mm): 870

Height (mm): 950

Dry weight (Kg): 390

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Compound

Engine manufacturer: Yanmar